
Waterdrop

Replacement Filter Installation Instruction WD-F2

Replacement for the following water filtration system:

Waterdrop X Series Reverse Osmosis System
WD-X8/WD-X10/WD-X12/WD-X14/WD-X16



Filter life: Up to 6 months (which may vary according to local water quality)

⚠ **NOTE:** Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection.

Getting Started:

With the leak-free design, filters could be replaced directly without cutting off power and water or using tools.

1. Before removing the filter, please turn off the faucet first and wait for 30s to fully release the internal pressure of the RO system, which makes the filter easier to remove and install.


2. Twist off the old filter in counterclockwise direction (If the filter cannot be removed at this time, it is necessary to close the ball valve, turn on the faucet, relieve the pressure inside the filter, and then remove the filter).

NOTE: After replacement of the F2 filter, it's recommended to press the center knob protruding at he top of the old filter to release pressure to avoid water spills. Get a towel or bucket to catch any water drips. When removing the filter, if the filter cannot be unscrewed counterclockwise, it can be removed with the aid of tools.


3. Remove the shrink wrap and protective cap from the new filter.

4. Insert the new filter into the housing, and align the arrow with the empty circle on the housing.

5. Apply slight forward pressure and rotate the filter clockwise 1/4 turn, until the arrow is aligned with the solid circle on the housing. You may hear a clicking sound when the filter is fitted in place.




Filter replacement



Filter installation

6. Hold the F2 filter life sign for 7 seconds until the system beeps and blue light stays on.

7. After resetting, the machine will automatically rinse for 5 minutes; there is no need to open the faucet.



Storage and Maintenance:

- Replace the filter regularly according to the light of the filter life indicator.
- Do not store the filter for a long time, and place it in a dry, cool place when not in use.
- The water source needs to meet the requirements of municipal tap water.
- Avoid placing it in direct sunlight.

Frequently Asked Questions:

Q: Why does filtered water taste weird ?

A: (1) The filter is about to expire. Check the indicator reminder to confirm and replace it; (2) The system hasn't been used for a long time. Turn on the RO faucet, and allow it to flush for a while before drink.

Q: What will happen if I do not change my filter when the filter life indicator light turns red?

A: Over-used filter will degrade the filtration performance, causing contaminants to leak back into the water and adversely affect your health. It's recommended to replace the filter if the filter life indicator turns red.

Q: Why is the filter life indicator still red after changing filter?

A: Forget or fail to reset the filter life indicator. Please reset it again. Hold the F2 filter reset indicator for 5 seconds until the system beeps and blue light stays on.

⚠ Warning:

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. Failure to follow instructions and operating specifications will void your warranty. Further, the manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)
E-mail: service@waterdropfilter.com

Made in China V002
Qingdao Ecopure Filter Co., Ltd.

24/7 365 Service