VEVOR®

TOUGH TOOLS, HALF PRICE

Technical Support and E-Warranty Certificate www.vevor.com/support

TRICYCLE

(Carbon steel frame - variable speed series)

SS002-1A；SS002-1B；SS002-1C；SS002-2A；SS002-2B；

SS002-2C； SS002-3A；SS002-3B；SS002-3C；SS002-3D；

SS002-4；SS002-5A；SS002-5B；SS002-5C；SS002-5D；

SS002-6A；SS002-6B；SS002-6C；

We continue to be committed to provide you tools with competitive price.
"Save Half", "Half Price" or any other similar expressions used by us only represents an estimate of savings you might benefit from buying certain tools with us compared to the major top brands and does not necessarily mean to cover all categories of tools offered by us. You are kindly reminded to verify carefully when you are placing an order with us if you are actually saving half in comparison with the top major brands.

VEVOR®

TOUGH TOOLS, HALF PRICE

Tricycle

Model: SS002-1A; SS002-1B; SS002-1C; SS002-2A; SS002-2B; SS002-2C; SS002-3A; SS002-3B; SS002-3C; SS002-3D; SS002-4; SS002-5A; SS002-5B; SS002-5C; SS002-5D; SS002-6A; SS002-6B; SS002-6C;

（The pictures are for reference only, please refer to the actual product）

NEED HELP? CONTACT US!

Have product questions? Need technical support? Please feel free to contact us: **Technical Support and E-Warranty Certificate**

www.vevor.com/support

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.

Dear Customer

Thank you for choosing our tricycle.This manual will show you how to assemble your tricycle.Please read the manual and follow it.The manualc ontains important information regarding assembing of the tricycle.If you have any misgiving,we recommend you to ask a tricycle mechanic for help.You also contact us via your shopping account.

CONTENTS

Tricycle Parts…….....03

Tools &Accessories….....04

Assembly Steps….....05~22

Waring&Safety…….....23~25

Warm tip: Products are constantly updated without notice. If some parts in the picture do not match the real ones, please refer to the real ones.

WARNING:

This product contains small parts. If swallowed, it will pose a choking hazard. Keep

these small parts away from children when assembling!

Tricycle Parts

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Tools&Accessories

TOOLS

A	B	C	D
Allen wrenchs	Wrench	Wrench (for wheels)	Screwdriver

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Assembly Steps

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps

1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.

4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps

1

2

3

4

5


6


HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver
		

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.

3. Tighten the screws.



4. Finished.

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps

1. Insert the stem into the Handlebar Tube.



2. Adjust the height of handlebar and tighten the screw.



3. Tighten the screw.



4. Finished

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench

Assembly Steps

1.Need to put the saddle post into the circled hole.



2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.



7. Adjust the height of the saddle.



8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

HOW TO ASSEMBLE THE SHIFTER CABLE

13

5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.

8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

HOW TO ASSEMBLE THE REAR BASKET

15

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.



6.Put the basket.

7. Tighten screws.



8. Finished.

9. Finished.

Waring&Safety

❷ Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

❶ Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

❷ Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.

It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Manufacturer: Shanghaimuxinmuyeyouxiangongsi
Address: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.
Imported to AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia
Imported to USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

EC	REP

E-CrossStu GmbH
Mainzer Landstr.69, 60329 Frankfurt am Main.

UK	REP

YH CONSULTING LIMITED.
C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames, Surrey, TW18 4AX

VEVOR®

TOUGH TOOLS, HALF PRICE

Technical Support and E-Warranty Certificate

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Assistance technique et certificat de garantie électronique www.vevor.com/support

TRICYCLE

(Cadre en acier au carbone - série à vitesse variable)

SS002-1ASS002-1BSS002-1CSS002-2ASS002-2B

SS002-2C SS002-3ASS002-3BSS002-3CSS002-3D

SS002-4SS002-5ASS002-5BSS002-5CSS002-5D

SS002-6ASS002-6BSS002-6C

Nous continuons à nous engager à vous fournir des outils à des prix compétitifs. « Économisez la moitié », « Moitié prix » ou toute autre expression similaire utilisée par nous ne représente qu'une estimation des économies que vous pourriez réaliser en achetant certains outils chez nous par rapport aux grandes marques et ne couvre pas nécessairement toutes les catégories d'outils que nous proposons. Nous vous rappelons de bien vouloir vérifier soigneusement lorsque vous passez une commande chez nous si vous économisez réellement la moitié par rapport aux grandes marques.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Tricycle

Modèle : SS002-1A ; SS002-1B ; SS002-1C ; SS002-2A ; SS002-2B ; SS002-2C ; SS002-3A ;

SS002-3BSS002-3CSS002-3DSS002-4SS002-5ASS002-5BSS002-5CSS002-5D

SS002-6ASS002-6BSS002-6C

(Les images sont fournies à titre indicatif uniquement, veuillez vous référer au produit réel)

BESOIN D'AIDE? CONTACTEZ-NOUS!

Vous avez des questions sur les produits ? Vous avez besoin d'assistance technique ? N'hésitez pas à nous contacter nous:

Assistance technique et certificat de garantie électronique

www.vevor.com/support

Machine Translated by Google

Il s'agit de la notice d'utilisation d'origine. Veuillez lire attentivement toutes les instructions du manuel avant de l'utiliser. VEVOR se réserve le droit d'interpréter clairement notre manuel d'utilisation. L'apparence du produit dépend du produit que vous avez reçu. Veuillez nous excuser, nous ne vous informerons plus en cas de mise à jour technologique ou logicielle de notre produit.

Cher client

Merci d'avoir choisi notre tricycle. Ce manuel vous montrera comment l'assembler

votre tricycle.Veuillez lire le manuel et le suivre.Le manuel contient des informations importantes

informations concernant l'assemblage du tricycle. Si vous avez des doutes, nous

nous vous recommandons de demander l'aide d'un mécanicien de tricycle. Vous pouvez également nous contacter via votre

compte d'achat.

CONTENU

Pièces de tricycle…….....03

Outils et accessoires….....04

Étapes d'assemblage….....05~22

Avertissement et sécurité…….....23~25

Conseil chaleureux : les produits sont constamment mis à jour sans préavis. Si certaines parties de la

les images ne correspondent pas aux vraies, veuillez vous référer aux vraies.

AVERTISSEMENT:

Ce produit contient de petites pièces. En cas d'ingestion, il présente un risque d'étouffement.

Machine Translated by Google

Gardez ces petites pièces hors de portée des enfants lors du montage !

Pièces de tricycle

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Outils et accessoires

TOOLS

A	B	C	D
Allen wrenchs	**Wrench**	**Wrench (for wheels)**	**Screwdriver**

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Étapes d'assemblage

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.



4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

❶ Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

❷ Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.

It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Fabricant : Shanghaimuxinmuyeyouxiangongsi

Adresse : Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Importé en Australie : SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australie

Importé aux États-Unis : Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

REPRÉSENTANT	DE LA CE

E-CrossStu GmbH

Mainzer Landstr.69, 60329 Francfort-sur-le-Main.

REPRÉSENTANT	DU ROYAUME-UNI

YH CONSULTING LIMITÉE.

A/S YH Consulting Limited Bureau 147, Centurion Maison, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Assistance technique et certificat de garantie électronique

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Technischer Support und E-Garantie-Zertifikat www.vevor.com/support

DREIRAD

(Rahmen aus Kohlenstoffstahl – Serie mit variabler Geschwindigkeit)

SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2Bÿ

SS002-2Cÿ SS002-3AÿSS002-3BÿSS002-3CÿSS002-3Dÿ

SS002-4ÿSS002-5AÿSS002-5BÿSS002-5CÿSS002-5Dÿ

SS002-6AÿSS002-6BÿSS002-6Cÿ

Wir sind weiterhin bestrebt, Ihnen Werkzeuge zu wettbewerbsfähigen Preisen anzubieten. „Sparen Sie die Hälfte“, „Halber Preis“ oder andere ähnliche Ausdrücke, die wir verwenden, stellen nur eine Schätzung der Ersparnis dar, die Sie beim Kauf bestimmter Werkzeuge bei uns im Vergleich zu den großen Topmarken erzielen können, und decken nicht unbedingt alle von uns angebotenen Werkzeugkategorien ab. Wir möchten Sie freundlich daran erinnern, bei Ihrer Bestellung bei uns sorgfältig zu prüfen, ob Sie im Vergleich zu den großen Topmarken tatsächlich die Hälfte sparen.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Dreirad

Modell: SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2BÿSS002-2CÿSS002-3Aÿ

SS002-3BÿSS002-3CÿSS002-3DÿSS002-4ÿSS002-5AÿSS002-5BÿSS002-5CÿSS002-5Dÿ

SS002-6AÿSS002-6BÿSS002-6Cÿ

ÿDie Bilder dienen nur als Referenz. Bitte beziehen Sie sich auf das tatsächliche Produkt.ÿ

Brauchen Sie Hilfe? Kontaktieren Sie uns!

Haben Sie Fragen zu den Produkten? Benötigen Sie technischen Support? Kontaktieren Sie uns

uns: **Technischer Support und E-Garantie-Zertifikat**

www.vevor.com/support

Machine Translated by Google

Dies ist die Originalanleitung. Bitte lesen Sie alle Anweisungen sorgfältig durch, bevor Sie das Gerät in Betrieb nehmen. VEVOR behält sich eine klare Auslegung unserer Bedienungsanleitung vor. Das Erscheinungsbild des Produkts richtet sich nach dem Produkt, das Sie erhalten haben. Bitte verzeihen Sie uns, dass wir Sie nicht erneut informieren, wenn es Technologie- oder Software-Updates für unser Produkt gibt.

Lieber Kunde

Vielen Dank, dass Sie sich für unser Dreirad entschieden haben. Dieses Handbuch zeigt Ihnen, wie Sie es zusammenbauen

Ihr Dreirad.Bitte lesen Sie das Handbuch und befolgen Sie es.Das Handbuch enthält wichtige

Informationen zur Montage des Dreirads. Wenn Sie irgendwelche Bedenken haben, wir

empfehlen wir Ihnen, einen Dreiradmechaniker um Hilfe zu bitten. Sie können uns auch über Ihre

Einkaufskonto.

INHALT

Dreiradteile…….....03

Werkzeuge & Zubehör….....04

Montageschritte….....05~22

Warnung und Sicherheit …….....23~25

Warmer Tipp: Produkte werden ständig ohne Vorankündigung aktualisiert. Wenn einige Teile in der

Die Bilder stimmen nicht mit den tatsächlichen überein. Bitte beziehen Sie sich auf die tatsächlichen Bilder.

WARNUNG:

Dieses Produkt enthält Kleinteile. Bei Verschlucken besteht Erstickungsgefahr.

Machine Translated by Google

Halten Sie diese Kleinteile beim Zusammenbau von Kindern fern!

Dreiradteile

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Werkzeuge & Zubehör

TOOLS

A	B	C	D
Allen wrenchs	Wrench	Wrench (for wheels)	Screwdriver

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
		
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Montageschritte

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

Warnung & Sicherheit

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

1. Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

2. Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

   Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.
It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Hersteller: Shanghaimuxinmuyeyouxiangongsi

Adresse: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, Shanghai 200000 CN.

Nach AUS importiert: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australien

Importiert in die USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

Vertreter der EG	E-CrossStu GmbH Mainzer Landstr.69, 60329 Frankfurt am Main.
UK REP	YH CONSULTING LIMITED. C/O YH Consulting Limited Office 147, Centurion Haus, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Technischer Support und E-Garantie-Zertifikat

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Supporto tecnico e certificato di garanzia elettronica www.vevor.com/support

TRICICLO

(Telaio in acciaio al carbonio - serie a velocità variabile)

SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2Bÿ

SS002-2Cÿ SS002-3AÿSS002-3BÿSS002-3CÿSS002-3Dÿ

SS002-4;SS002-5A;SS002-5B;SS002-5C;SS002-5D;

SS002-6AÿSS002-6BÿSS002-6Cÿ

Continuiamo a impegnarci per fornirvi strumenti a prezzi competitivi.
"Risparmia la metà", "Metà prezzo" o qualsiasi altra espressione simile da noi utilizzata rappresenta solo una stima del risparmio che potresti ottenere acquistando determinati utensili con noi rispetto ai principali marchi principali e non significa necessariamente coprire tutte le categorie di utensili da noi offerti. Ti ricordiamo gentilmente di verificare attentamente quando effettui un ordine con noi se stai effettivamente risparmiando la metà rispetto ai principali marchi principali.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Triciclo

Modello: SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2BÿSS002-2CÿSS002-3Aÿ

SS002-3BÿSS002-3CÿSS002-3DÿSS002-4ÿSS002-5AÿSS002-5BÿSS002-5CÿSS002-5Dÿ

SS002-6AÿSS002-6BÿSS002-6Cÿ

(Le immagini sono solo di riferimento, fare riferimento al prodotto reale)

HAI BISOGNO DI AIUTO? CONTATTACI!

Hai domande sui prodotti? Hai bisogno di supporto tecnico? Non esitare a contattarci noi:

Supporto tecnico e certificato di garanzia elettronica

www.vevor.com/support

Machine Translated by Google

Questa è l'istruzione originale, si prega di leggere attentamente tutte le istruzioni del manuale prima di utilizzare. VEVOR si riserva una chiara interpretazione del nostro manuale utente. L'aspetto del prodotto sarà soggetto al prodotto ricevuto. Vi preghiamo di perdonarci se non vi informeremo di nuovo se ci sono aggiornamenti tecnologici o software sul nostro prodotto.

Gentile Cliente

Grazie per aver scelto il nostro triciclo. Questo manuale ti mostrerà come montarlo

il tuo triciclo. Leggi il manuale e seguilo. Il manuale contiene informazioni importanti

informazioni riguardanti il montaggio del triciclo.Se avete qualche dubbio,noi

ti consigliamo di chiedere aiuto a un meccanico di tricicli. Puoi anche contattarci tramite il tuo

conto acquisti.

CONTENUTO

Parti del triciclo…….....03

Strumenti e accessori….....04

Fasi di assemblaggio….....05~22

Attenzione e sicurezza…….....23~25

Suggerimento: i prodotti vengono costantemente aggiornati senza preavviso. Se alcune parti nel

Le immagini non corrispondono a quelle reali, fare riferimento a quelle reali.

AVVERTIMENTO:

Questo prodotto contiene piccole parti. Se ingerito, può rappresentare un rischio di soffocamento. Tenere

Machine Translated by Google

queste piccole parti lontano dalla portata dei bambini durante il montaggio!

Parti del triciclo

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Strumenti e accessori

TOOLS

A	B	C	D
Allen wrenchs	Wrench	Wrench (for wheels)	Screwdriver

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
		
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Fasi di assemblaggio

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

Attenzione e sicurezza

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

❶ Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

❷ Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.
It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Produttore: Shanghaimuxinmuyeyouxiangongsi
Indirizzo: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.
Importato in AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia
Importato negli USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

Rappresentante della CE	E-CrossStu GmbH Mainzer Landstr.69, 60329 Francoforte sul Meno.

RAPPRESENTANZA DEL REGNO UNITO	CONSULENZA YH LIMITATA. C/O YH Consulting Limited Ufficio 147, Centurion Casa, London Road, Staines-upon-Thames, Surrey, TW184AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Supporto tecnico e certificato di garanzia elettronica

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Soporte técnico y certificado de garantía electrónica www.vevor.com/support

TRICICLO

(Cuadro de acero al carbono - Serie de velocidad variable)

SS002-1ASS002-1BSS002-1CSS002-2ASS002-2B

SS002-2C SS002-3ASS002-3BSS002-3CSS002-3D

SS002-4SS002-5ASS002-5BSS002-5CSS002-5D

SS002-6ASS002-6BSS002-6C

Seguimos comprometidos a brindarle herramientas a precios competitivos.
"Ahorre la mitad", "mitad de precio" o cualquier otra expresión similar que utilicemos solo representa una estimación del ahorro que podría obtener al comprar ciertas herramientas con nosotros en comparación con las principales marcas y no necesariamente significa que cubra todas las categorías de herramientas que ofrecemos. Le recordamos que, al realizar un pedido con nosotros, verifique cuidadosamente si realmente está ahorrando la mitad en comparación con las principales marcas.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Triciclo

Modelo: SS002-1ASS002-1BSS002-1CSS002-2ASS002-2BSS002-2CSS002-3A

SS002-3BSS002-3CSS002-3DSS002-4SS002-5ASS002-5BSS002-5CSS002-5D

SS002-6ASS002-6BSS002-6C

(Las imágenes son solo de referencia, consulte el producto real)

¿NECESITA AYUDA? ¡CONTÁCTENOS!

¿Tiene preguntas sobre el producto? ¿Necesita asistencia técnica? No dude en ponerse en contacto con nosotros.

a nosotros: Soporte técnico y certificado de garantía electrónica

www.vevor.com/support

Machine Translated by Google

Estas son las instrucciones originales, lea atentamente todas las instrucciones del manual antes de utilizar el producto. VEVOR se reserva una interpretación clara de nuestro manual de usuario. La apariencia del producto estará sujeta al producto que recibió. Perdónenos por no informarle nuevamente si hay actualizaciones de tecnología o software en nuestro producto.

Estimado cliente

Gracias por elegir nuestro triciclo. Este manual le mostrará cómo ensamblarlo.

Su triciclo. Lea el manual y sígalo. El manual contiene información importante.

información sobre el montaje del triciclo. Si tiene alguna duda, le atenderemos.

Le recomendamos que pida ayuda a un mecánico de triciclos. También puede ponerse en contacto con nosotros a través de su

cuenta de compras.

CONTENIDO

Partes del triciclo…….....03

Herramientas y accesorios….....04

Pasos de montaje….....05~22

Advertencias y seguridad…….....23~25

Consejo: Los productos se actualizan constantemente sin previo aviso. Si algunas partes del

La imagen no coincide con las reales, consulte las reales.

ADVERTENCIA:

Este producto contiene piezas pequeñas. Si se ingieren, pueden provocar asfixia.

Machine Translated by Google

¡Mantenga estas piezas pequeñas fuera del alcance de los niños durante el montaje!

Partes del triciclo

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Herramientas y accesorios

TOOLS

A	B	C	D
Allen wrenchs	**Wrench**	**Wrench (for wheels)**	**Screwdriver**

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
		
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Pasos de montaje

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.



4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

1. Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

2. Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

   Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.

It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Fabricante: Shanghaimuxinmuyeyouxiangongsi

Dirección: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Importado a AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia

Importado a EE. UU.: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

REPRESENTANTE CE

E-CrossStu GmbH

Mainzer Landstr.69, 60329 Fráncfort del Meno.

REPRESENTANTE DEL REINO UNIDO

YH CONSULTING LIMITADA.

C/O YH Consulting Limited Oficina 147, Centurion Casa, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Soporte técnico y certificado de garantía electrónica

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Wsparcie techniczne i certyfikat gwarancji elektronicznej www.vevor.com/support

TRYCYKL

(Rama ze stali węglowej - seria o zmiennej prędkości)

SS002-1A;SS002-1B;SS002-1C;SS002-2A;SS002-2B;

SS002-2C; SS002-3A; SS002-3B; SS002-3C; SS002-3D;

SS002-4;SS002-5A;SS002-5B;SS002-5C;SS002-5D;

SS002-6A; SS002-6B; SS002-6C;

Nadal staramy się oferować Państwu narzędzia w konkurencyjnych cenach. „Oszczędź połowę", „Połowa ceny" lub inne podobne wyrażenia używane przez nas stanowią jedynie szacunkowe oszczędności, jakie możesz uzyskać, kupując u nas określone narzędzia w porównaniu z głównymi markami i niekoniecznie oznaczają one objęcie wszystkich kategorii narzędzi oferowanych przez nas. Uprzejmie przypominamy, aby dokładnie sprawdzić, czy składając u nas zamówienie faktycznie oszczędzasz połowę w porównaniu z głównymi markami.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Trycykl

Modelu: SS002-1A; SS002-1B; SS002-1C; SS002-2A; SS002-2B; SS002-2C; SS002-3A; SS002-3B;SS002-3C;SS002-3D;SS002-4;SS002-5A;SS002-5B;SS002-5C;SS002-5D; SS002-6A; SS002-6B; SS002-6C;

(Zdjęcia mają charakter poglądowy, prosimy zapoznać się z rzeczywistym produktem)

POTRZEBUJESZ POMOCY? SKONTAKTUJ SIĘ Z NAMI!

Masz pytania dotyczące produktu? Potrzebujesz wsparcia technicznego? Skontaktuj się z nami nas:

Wsparcie techniczne i certyfikat e-gwarancji

www.vevor.com/support

Machine Translated by Google

To jest oryginalna instrukcja, przed użyciem należy uważnie przeczytać wszystkie instrukcje. VEVOR zastrzega sobie jasną interpretację naszej instrukcji obsługi. Wygląd produktu będzie zależał od produktu, który otrzymałeś. Prosimy o wybaczenie, że nie poinformujemy Cię ponownie, jeśli w naszym produkcie pojawią się jakiekolwiek aktualizacje technologiczne lub oprogramowania.

Szanowny Kliencie

Dziękujemy za wybranie naszego trójkołowca. Niniejsza instrukcja pokaże Ci, jak go złożyć.

trójkołowego. Przeczytaj instrukcję i postępuj zgodnie z nią. Instrukcja zawiera ważne informacje

informacje dotyczące montażu trójkołowca. Jeśli masz jakiekolwiek wątpliwości,

polecamy zwrócić się o pomoc do mechanika trójkołowego. Możesz się z nami skontaktować również za pośrednictwem

konto zakupowe.

ZAWARTOŚĆ

Części do trójkołowców.....03

Narzędzia i akcesoria.....04

Etapy montażu.....05~22

Ochrona i bezpieczeństwo.....23~25

Ciepła wskazówka: Produkty są stale aktualizowane bez powiadomienia. Jeśli niektóre części w

Zdjęcia nie odpowiadają rzeczywistym, prosimy zapoznać się z prawdziwymi zdjęciami.

OSTRZEŻENIE:

Ten produkt zawiera małe części. W przypadku połknięcia istnieje ryzyko zadławienia. Przechowywać

Machine Translated by Google

Podczas montażu trzymaj te małe części w miejscu niedostępnym dla dzieci!

Części do trójkołowców

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Narzędzia i akcesoria

TOOLS

A	B	C	D
Allen wrenchs	**Wrench**	**Wrench (for wheels)**	**Screwdriver**

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
		
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Kroki montażu

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.

3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

1. Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

2. Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

   Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.

It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Producent: Shanghaimuxinmuyeyouxiangongsi

Adres: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, szanghaj 200000 CN.

Importowane do AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia

Importowane do USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

Przedstawiciel UE	E-CrossStu GmbH Mainzer Landstr.69, 60329 Frankfurt nad Menem.

REP WIELKIEJ BRYTANII	YH CONSULTING LIMITED. C/O YH Consulting Limited Biuro 147, Centurion Dom, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Wsparcie techniczne i certyfikat e-gwarancji

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Technische ondersteuning en e-garantiecertificaat www.vevor.com/support

DRIEWIELER

(Koolstofstalen frame - serie met variabele snelheid)

SS002-1A; SS002-1B; SS002-1C; SS002-2A; SS002-2B;

SS002-2C; SS002-3A; SS002-3B; SS002-3C; SS002-3D;

SS002-4;SS002-5A;SS002-5B;SS002-5C;SS002-5D;

SS002-6A; SS002-6B; SS002-6C;

Wij streven er voortdurend naar om u gereedschappen tegen concurrerende prijzen te leveren. "Save Half", "Half Price" of andere soortgelijke uitdrukkingen die wij gebruiken, geven alleen een schatting van de besparingen die u kunt behalen door bepaalde gereedschappen bij ons te kopen in vergelijking met de grote topmerken en betekent niet noodzakelijkerwijs dat alle categorieën gereedschappen die wij aanbieden, worden gedekt. Wij herinneren u eraan om zorgvuldig te controleren of u daadwerkelijk de helft bespaart in vergelijking met de grote topmerken wanneer u een bestelling bij ons plaatst.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Driewieler

Model: SS002-1A;SS002-1B;SS002-1C;SS002-2A;SS002-2B;SS002-2C;SS002-3A;

SS002-3B;SS002-3C;SS002-3D;SS002-4;SS002-5A;SS002-5B;SS002-5C;SS002-5D;

SS002-6A; SS002-6B; SS002-6C;

(De afbeeldingen zijn alleen ter referentie, raadpleeg het daadwerkelijke product)

HULP NODIG? NEEM CONTACT MET ONS OP!

Heeft u vragen over het product? Heeft u technische ondersteuning nodig? Neem dan gerust contact met ons op ons:

Technische ondersteuning en e-garantiecertificaat

www.vevor.com/support

Machine Translated by Google

Dit is de originele instructie, lees alle handleidingen zorgvuldig door voordat u het product gebruikt. VEVOR behoudt zich een duidelijke interpretatie van onze gebruikershandleiding voor. Het uiterlijk van het product is afhankelijk van het product dat u hebt ontvangen. Vergeef ons dat we u niet opnieuw zullen informeren als er technologie- of software-updates voor ons product zijn.

Beste klant

Bedankt dat u voor onze driewieler hebt gekozen. Deze handleiding laat u zien hoe u deze in elkaar zet.

uw driewieler. Lees de handleiding en volg deze op. De handleiding bevat belangrijke

informatie over het monteren van de driewieler. Als u twijfels heeft, kunnen wij u helpen

Ik raad u aan om een driewielermonteur om hulp te vragen. U kunt ook contact met ons opnemen via uw

winkelaccount.

INHOUD

Driewieleronderdelen…….....03

Gereedschappen en accessoires….....04

Montagestappen….....05~22

Waarschuwing en veiligheid…….....23~25

Warme tip: Producten worden voortdurend bijgewerkt zonder voorafgaande kennisgeving. Als sommige onderdelen in de

De foto's komen niet overeen met de werkelijkheid. Bekijk de echte foto's.

WAARSCHUWING:

Dit product bevat kleine onderdelen. Bij inslikken kan er verstikkingsgevaar ontstaan.

Machine Translated by Google

Houd deze kleine onderdelen bij de montage buiten bereik van kinderen!

Driewieler onderdelen

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Gereedschappen en accessoires

TOOLS

A	B	C	D
Allen wrenchs	**Wrench**	**Wrench (for wheels)**	**Screwdriver**

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Montagestappen

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

❶ Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

❷ Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.
It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Fabrikant: Shanghaimuxinmuyeyouxiangongsi

Adres: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Geïmporteerd naar AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australië

Geïmporteerd naar de VS: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

EC-REP

E-CrossStu GmbH

Mainzer Landstr.69, 60329 Frankfurt am Main.

VK REP

YH CONSULTING LIMITED.

C/O YH Consulting Limited Kantoor 147, Centurion Huis, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Technische ondersteuning en e-garantiecertificaat

www.vevor.com/support

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Teknisk support och e-garanticertifikat www.vevor.com/support

TRICYKEL

(Ram i kolstål - serie med variabel hastighet)

SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2Bÿ

SS002-2Cÿ SS002-3AÿSS002-3BÿSS002-3CÿSS002-3Dÿ

SS002-4ÿSS002-5AÿSS002-5BÿSS002-5CÿSS002-5Dÿ

SS002-6AÿSS002-6BÿSS002-6Cÿ

Vi fortsätter att vara engagerade i att ge dig verktyg till konkurrenskraftiga priser. "Spara hälften", "halva priset" eller andra liknande uttryck som används av oss representerar bara en uppskattning av besparingar du kan dra nytta av att köpa vissa verktyg hos oss jämfört med de stora toppmärkena och betyder inte nödvändigtvis att täcka alla kategorier av verktyg som erbjuds av oss. Du påminns vänligen om att noggrant kontrollera när du gör en beställning hos oss om du faktiskt sparar hälften i jämförelse med de främsta stora varumärkena.

Machine Translated by Google

VEVOR®
TOUGH TOOLS, HALF PRICE

Trehjuling

Modell: SS002-1AÿSS002-1BÿSS002-1CÿSS002-2AÿSS002-2BÿSS002-2CÿSS002-3Aÿ

SS002-3BÿSS002-3CÿSS002-3DÿSS002-4ÿSS002-5AÿSS002-5BÿSS002-5CÿSS002-5Dÿ

SS002-6AÿSS002-6BÿSS002-6Cÿ

ÿBilderna är endast för referens, vänligen hänvisa till den faktiska produktenÿ

BEHÖVER HJÄLP? KONTAKTA OSS!

Har du produktfrågor? Behöver du teknisk support? Kontakta gärna

oss: **Teknisk support och e-garanticertifikat**

www.vevor.com/support

Machine Translated by Google

Detta är den ursprungliga instruktionen, läs alla instruktioner noggrant innan du använder den. VEVOR reserverar sig för en tydlig tolkning av vår användarmanual. Utseendet på produkten är beroende av den produkt du fått. Ursäkta oss att vi inte kommer att informera dig igen om det finns någon teknik eller mjukvaruuppdateringar på vår produkt.

Kära kund

Tack för att du valde vår trehjuling. Den här manualen visar hur du monterar din trehjuling. Läs bruksanvisningen och följ den. Manualen är viktig information angående montering av trehjulingen. Om du har några farhågor kan vi rekommenderar dig att fråga en trehjulingsmekaniker om hjälp. Du kontaktar oss också via din shoppingkonto.

INNEHÅLL

Trehjulingsdelar……..... 03

Verktyg och tillbehör..... 04

Monteringssteg ....05~22

Varning och säkerhet..... .....23~25

Varmt tips: Produkterna uppdateras ständigt utan förvarning. Om vissa delar i bilden stämmer inte överens med de riktiga, se de riktiga.

VARNING:

Denna produkt innehåller små delar. Om den sväljs kommer den att utgöra en kvävningsrisk. Hålla

Machine Translated by Google

dessa små delar borta från barn vid montering!

Trehjuling delar

Check all parts of the tricycle before assembly. If any parts are missing or damaged, please contact us via your account order.

NO.	Parts Name
1	Rear Derailleur
2	Rear Axle
3	Rear Wheels
4	Nut Caps
5	Frame
6	Chain
7	Chain Cover
8	Front Fender
9	Front Wheel
10	Rear Fender
11	Handlebar
12	Front Brake
13	Seat Post
14	Saddle
15	Pedal
16	Shifter & Shifter Cable
17	Rear Brake Cable
18	Rear Basket
19	Basket Accessories
20	Front Reflector
21	Rear Reflector
22	Spoke Reflector
23	Bell

Machine Translated by Google

Verktyg och tillbehör

TOOLS

A	B	C	D
Allen wrenchs	Wrench	Wrench (for wheels)	Screwdriver

Machine Translated by Google

Accessories

- Some screws have been pre-installed in the corresponding positions.

F	G	H	I	J
				
Rear left/right wheel screw and shaft sleeve x1	Front wheel screw and safety buckle x2	Brake spring x1	4 screws and 4 nuts for rear basket	Basket metal fixing plate x12

K	L	M
		
Front fender bracket screw x1,Front fender fixing front fork screw x1	Rear fender bracket screws x8	Rear fender screws x6

Monteringssteg

Machine Translated by Google

HOW TO ASSEMBLE THE REAR DERAILLEUR

01

Parts And Tools

Rear Derailleur	Rear Axle	Allen wrench

Assembly Steps



1. screw hole of the rear axle.

2. Put the bolt of the rear derailleur into the hole of the rear axle.

3. Tighten with a Allen wrench.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR WHEELS

02

Parts And Tools

Assembly Parts	Rear Wheels	Nut caps	Wrench

Assembly Steps

1. Differentiate the left or right wheel according to the shape of the screw hole.



2. Differentiate the left or right of the rear axle According to the rear axle's ends shapes.

3. Insert axle right end into the right wheel.

4. Put the gasket , nut and tighten with a wrench.

5. Put the metal tube on axle left end.

6.Follow Step 3.

7.Follow Step 4.

8. Cover the rear axle nut caps.

9. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE REAR AXLE

03

Parts And Tools

Assembly Parts	Frame	Wrench	Wrench

Assembly Steps

1.Loosen the screws.

2.Connect the rear axle and frame, as shown.

3.Assemble rear axle and frame.



4.Display

5.Tighten the screws.

6.Tighten the nuts.

7.All screws and nuts are tightened.

8.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN

04

Parts And Tools

Assembly Parts	Chain	Chain magic buckle

Assembly Steps



Machine Translated by Google

HOW TO ASSEMBLE THE CHAIN COVER

05

Parts And Tools

Assembly Parts	Chain Cover	Screwdriver

Assembly Steps

1. Locate the two screw holes on the frame.



2. Put on the chain cover and tighten the screws with a screwdriver

3. Tighten the second screw

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT WHEEL

06

Parts And Tools

Fork	Front Fender	Front Wheel	Tools

Assembly Steps



1.Assemble the front fender.

2.Tighten the screw.

3.Assemble front wheel and frame.

4.Assemble the washer.

5.Assemble the fender holder.

6.Tighten the screw.

7. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE BELL AND REFLECTORS

07

Parts And Tools

Bell	Front & Rear Reflector	Wheel Reflector	Screwdriver

Assembly Steps

1.Attach the bell on the handlebar.

2. Tighten the screw.

3. Assemble the front reflector.

4. Tighten the screw.

5. Finished.

6. Attach reflectors on rear fenders.

7.Tighten reflector with screw.

8. Attach the reflectors on the wheel.

9.Follow step 8.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR FENDER

08

Parts And Tools

Rear Axle	Rear Fender	Screwdriver

Assembly Steps

1.Notice the circled hole on the rear axle.

2.Prepare fenders and holders.



3. Tighten the screws.



4. Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE HANDLEBAR

09

Parts And Tools

Handlebar Tube	Handlebar	Screwdriver

Assembly Steps



1. Insert the stem into the Handlebar Tube.

2. Adjust the height of handlebar and tighten the screw.

3. Tighten the screw.

4. Finished

Machine Translated by Google

HOW TO ASSEMBLE THE SADDLE

10

Parts And Tools

Saddle Tube	Saddle Post	Saddle	Wrench
			

Assembly Steps

1.Need to put the saddle post into the circled hole.

2. Loosen the screw.

3. Insert saddle post.



4. Tighten the screw.

5. Loose the saddle post clamp.

6. Insert the saddle.

7. Adjust the height of the saddle.

8. Adjust the angle of the saddle.

9. Tighten the saddle post clamp.

Machine Translated by Google

HOW TO ASSEMBLE THE PEDALS

11

Parts And Tools

Crank	Pedals

Assembly Steps

1.Differentiate the pedals.

2.Tighten pedals.

3.Follow step 2.

4.Finished

Machine Translated by Google

HOW TO ASSEMBLE THE FRONT BRAKE

12

Parts And Tools

Left Brake Lever	Front Brake	Allen wrench
		

Assembly Steps



Connect the Brake wire to the Brake Lever

① Rotate all parts of the brake until all the slots are in a straight line.

② Squeeze the brake lever.

③ Take the brake wire into the slots the brake.

④ Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.



Assemble a front brake

① Loosen the screw.

② Insert brake wire and adjust the length of remainder.

③ Tighten the screw NO.1.



Adjust the brake pads to the correct position



Tighten the screw.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE

13

Parts And Tools

Shifter	Shifter Tubes	Rear Derailleur

Assembly Steps



1.Insert a shifter wire into a shifter tube.

2.Insert the derailleur cabel into the shift lever and fix it.

3.Run the shifter wire through the holes on the frame.

4.Insert the shifter wire through the hole of derailleur.

Machine Translated by Google

HOW TO ASSEMBLE THE SHIFTER CABLE



5.Bear down the shifter wire with the sheet.

6.Adjust front shifter to 7th speed when assemble the derailleur.

7.Adjust the chain to the smallest gear when assemble the derailleur.



8.Straighten the shifter wire and tighten the screw.

9.Adjust the derailleur by adjusting screws.



10.Rectify derailleur position by adjusting screws.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

Parts And Tools

Rear Brake Wire	Right Brake Lever	Rear Brake	Wrench
			

Assembly Steps

1.Squeeze the brake lever.

2. Put the wire tip into the hole of the lever.



3. Rotate all parts of the brake until all the slots are in a straight line.

4. Pull the wire and rotate all parts of the brake to make sure the wire doesn't fall out.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BRAKE

14

5. Insert the brake tube into the brake lever.



6.Run the wire through hole NO.1.

7.Put on the brake spring.



8.Run the wire through hole NO.2.

9. Tighten the screw.

10.Finished.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

15

Parts And Tools

Rear Axle	Basket	Basket parts	Screwdriver
			

Assembly Steps



1.Assemble the basket as indicated in the picture and secure with metal sheets.

Machine Translated by Google

HOW TO ASSEMBLE THE REAR BASKET

2.Basket pieces method.

3. Secure with metal sheets.

4.Finished.

5.Four holes for fixing basket.

6.Put the basket.

7. Tighten screws.

8. Finished.

9. Finished.

Machine Translated by Google

Varning och säkerhet

2 Safety

SAFETY SIGNAL WORDS

The following safety signal words indicate a safety message. The symbol alerts you to potential hazards. Failure to follow the warning may result in damage to property, injury, or death.

This manual contains many Warnings and Cautions concerning the consequences of failure to follow safety warnings. Because any fall can result in serious injury or even death, we do not repeat the warning of possible injury or death whenever the risk of falling is mentioned.

⚠ WARNING!

Indicates a hazard or unsafe practice that will result in severe injury or death. Failure to read, understand and follow the safety information in this manual may result in serious injury or death.

⚠ CAUTION!

Indicates a hazard or unsafe practice that could result in minor injury.

NOTICE

Indicates a hazard unrelated to personal injury, such as property damage.

USER RESPONSIBILITY

⚠ WARNING!

Do not install any kind of power plant or internal combustion engine to a bicycle. Adapting a bicycle in this manner poses an extreme safety risk to rider and could result in loss of control or death.

All persons assembling, using, and maintaining the bicycle must read and understand the safety warnings and operating instructions in this manual before using the bicycle.

It is the responsibility of the user, or in the case of a child rider, an adult, to ensure the bicycle is properly maintained and in proper operating condition. Doing so will reduce the risk of injury. Always conduct regular maintenance and inspection of your bicycle. Complete the Safety Checklist at the end of this section before each use.

A responsible adult must always supervise the use of the bicycle by a child. You must ensure:

- The child is wearing the proper protective attire and approved bicycle helmet.
- The child is seated securely and the bicycle is properly fitted to the child.
- The child understands applicable laws and common sense rules of safe responsible bicycling.

Quick-release Levers

⚠ WARNING!

Improper setup or maintenance of the quick-release levers may result in an unexpected movement, loss of control, and serious injury or death. Before riding always check that the quick-release lever is firmly locked in place and the seat does not move.

Wheels

❶ Some bicycles will come equipped with quick-release levers for the front wheel. The wheels must be securely locked. Ensure the wheel quick-release lever is firmly locked in place. **Figure 1.3**

Seat Post

❷ Ensure the seat post's ***minimum insertion marks*** are **not** visible above the quick-release seat clamp and the clamp is locked in place.

Note: See ***Section 4: Adjusting the Seat Height*** if adjustments are needed.



Figure 1.3

Machine Translated by Google

PERSONAL SAFETY

⚠ WARNING!

Riding a bicycle without protective gear, clothing, or a helmet may result in serious injury or death. Always wear protective gear, clothing, and helmet when riding the bicycle. Ensure protective gear does not interfere with steering, braking, and pedaling.

Protective Gear and Clothing

Always wear: Figure 1.4

- Colors that are easily seen and, if possible, reflective clothing.
- Clothing appropriate for the weather conditions.
- Use of protective gear such as pads for the knees and elbows is highly recommended for children.
- A properly fitted, ASTM or SNELL approved, bicycle helmet shall be worn at all times by riders of the bicycle.

Do not wear:

- Loose clothing parts, strings, or jewelry that may become entangled with moving parts on the bicycle or interfere with handling of the bicycle.
- Pants with loose pant legs. If necessary, always tuck pant legs into a sock or use a leg band to avoid the clothing becoming caught in the drive chain.
- Shoes with untied shoe laces.



Figure 1.4

Helmet Use

Important! Many states and provinces have passed helmet laws. Make sure you know your state's helmet laws. It is your job to enforce these rules with your children. Even if your state/province does not have a children's helmet law, it is recommended that everyone wear a helmet when cycling. When riding with a child carrier seat or trailer, children must wear a helmet.
It is strongly advised that a properly fitting, ASTM or SNELL approved, bicycle safety helmet be worn at all times when riding your bicycle. In addition, if you are carrying a passenger in a child safety seat, they must also be wearing a helmet.

The correct helmet should: Figure 1.5

- Be comfortable
- Have good ventilation
- Fit correctly
- Cover forehead

Incorrect helmet position: Figure 1.6

- Helmet ***does not*** cover the forehead

Figure 1.5

Figure 1.6

Machine Translated by Google

Reflectors

⚠ WARNING!

Missing, damaged, or dirty reflectors will affect the ability of others to see and recognize you as a moving bicyclist, increasing the risk of being hit, serious injury or death. Always check the reflectors are in place and make sure they are clean, straight, unbroken and securely mounted before riding the bicycle.

Important! Federal regulations require every bicycle over 16 inches to be equipped with front, rear, wheel, and pedal reflectors. Many states require specific safety devices. It is your responsibility to familiarize yourself with the laws of the state where you ride and to comply with all applicable laws, including properly equipping yourself and your bike as the law requires. Bicycles under 16 inches are considered "sidewalk bicycles" and may not be fitted with reflectors. These bicycles should **not** be ridden on streets, at night or unsupervised by an adult.

Check and confirm the front and rear reflectors are in the correct position: **Figure 1.7**

- **Front Reflector:** Should aim forward (when viewed from above) and be mounted so it is within 5 degrees of vertical.
- **Rear Reflector:** Should aim straight back (when viewed from above) and be mounted so it is within 5 degrees of vertical.



Figure 1.7

RIDING SAFETY

⚠ WARNING!

Riding the bicycle in unsafe conditions (i.e. at night), in an unsafe manner, or disregarding traffic laws may result in an unexpected movement, loss of control, and serious injury or death.

General Safety

- Familiarize yourself with all the bicycle's features before riding. Practice gear shifts, braking, and the use of toe clips and straps, if installed.
- Always ride defensively in a predictable, straight line. Never ride against traffic.
- Expect the unexpected (e.g., opening car doors or cars backing out of concealed driveways).
- Take extra care at intersections and when preparing to pass other vehicles.
- Maintain a comfortable stopping distance from all other riders, vehicles and objects. Safe braking distances and forces are subject to the prevailing weather conditions. Do not lock up the brakes. When braking, always apply the rear brake first, then the front. The front brake is more powerful and if it is not correctly applied, you may lose control and fall.
- Always use the correct hand signals to indicate turning or stopping.
- Obey the traffic laws (e.g., stopping at a red light or stop sign, giving way to pedestrians).
- Wear proper riding attire, reflective if possible, and avoid open toe shoes.
- Do not use items that may restrict your hearing and vision.
- Do not carry packages or passengers that will interfere with your visibility or control of the bicycle.

Road Conditions

- Be aware of road conditions. Concentrate on the path ahead. Avoid pot holes, gravel, wet road markings, oil, curbs, speed bumps, drain grates and other obstacles.
- Cross train tracks at a 90 degree angle or walk your bicycle across.

Wet Weather

- When riding in wet weather always wear reflective clothing and use safety lights to enhance visibility.
- Exercise extreme caution when riding in wet conditions.
- Ride at a slower speed. Turn corners gradually and avoid sudden braking.
- Brake earlier, it will take a longer distance to stop.
- Pot holes and slippery surfaces such as line markings and train tracks all become more hazardous when wet.

Machine Translated by Google

Tillverkare: Shanghaimuxinmuyeyouxiangongsi

Adress: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Importerad till AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australien

Importerad till USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

EC REP

E-CrossStu GmbH

Mainzer Landstr.69, 60329 Frankfurt am Main.

UK REP

YH CONSULTING LIMITED.

C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames, Surrey, TW18 4AX

Machine Translated by Google

VEVOR®

TOUGH TOOLS, HALF PRICE

Teknisk support och e-garanticertifikat

www.vevor.com/support