

[illegible]

SETTING UP



Device A

Connecting device



Device B

Device being controlled

1 Point (USB) port and connect the GL400T80C to a power source to power it.



▲ Point (USB) port

▲ Power source

2 Use a **USB cable** to connect the GL400T80C, HDMI B port to the HDMI port of Device B. Use another **USB cable** to connect the GL400T80C, using port 2 to the monitor of Device A.



Desktop Computer

GL400T80C

HDMI B port

HDMI port

3 Connect the GL400T80C Type-C port to the USB interface of the Device B using a **Type-C cable**.



Desktop Computer

GL400T80C

Type-C port

USB interface

4 **Internet Connection**

LAN: Plug a network cable into the LAN port, and connect to an existing local network.



GL400T80C

LAN port

LAN cable

LAN interface

Wi-Fi: All the GL400T80C has touchscreen, voice call, and connect to an existing local network.



GL400T80C

Wi-Fi port

Wi-Fi interface

Bluetooth: All the GL400T80C has Bluetooth. It can be connected to a Bluetooth device.



GL400T80C

Bluetooth port

Bluetooth interface

		产品名称	GL-RM10RC 海外英文说明书
深圳市广联智通科技有限公司		物料编码	505-0xxx
设计	朱志豪	单位/比例	mm/1:1
审核	朱哲宇/郑超	尺寸	78*95mm±1mm
标准化	叶彩霞	材质	128g铜版纸/单色印刷/5折6页/过油
批准	邓珊珊	日期	ver. 2026/02/09