

PG-F02 Remote Control Specification

1. Product Overview

This software is the embedded software for the equipment cascade control remote. It is used in conjunction with various cascade alarms to enable testing, silencing, alarm source localization, and cascade setting functions for the cascade alarms

2. Product Appearance



TEST

Test Button: Triggers all devices to execute a test simultaneously (Sound + Light + LCD Display)

MUTE

Mute Button: Synchronously mutes the alarm sound of all devices (10 minutes of silence)

LOCATE

Alarm Source Localization Button: During an alarm, only the sound and light of the source device are retained, while other devices remain silent

Pair

Pairing: Add the remote control to the cascade group

4. Other Requirements

Communication Method: RF433 (FSK)

Low Power Consumption Requirement: Refer to the previous remote control

§ 15.105 Information to the user.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

* RF warning for Portable device:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

§ 15.19 Labelling requirements.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

§ 15.21 Information to user.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.