



ThinPAD International CO.,LTD

①	Micro SD	②	DC Jack
③	Pogo connector	④	Mini USB
⑤	3.5mm Audio Jack	⑥	Power button
⑦	Speaker	⑧	Fan
⑨	battery LED	⑩	Power/WiFi LED

Product	Description
Dimension	325.0 (L) * 197.0 (W) * 39.7 (H)mm
CPU	Intel® N100, 3.4 GHz, 4 core 4 threads, TDP 6W
LCD Panel	10.1"screen (MIPI), 800 * 1280 resolution HD WXGA; 10 : 16 aspect ratio, luminance 300CD/m² (Default); 10.1"screen (MIPI), 1200 * 1920 resolution FHD WUXGA; 10 : 16 aspect ratio, luminance 300CD/m² (Option)
Touch Panel	Capacitive 10 points touch, interface I2C, 1K07 hardness
Memory	4GB LPDDR5 (data rate 4800Mb/s) on board 315 balls memory module, support 4GB to 16GB
Storage	128GB SSD M.2 2242 key M, support to 1TB (Option)
Card Reader	Support secure digital MSD card 8GB~512GB
Front Camera	500MP + AF, USB interface (Option)
Wi-Fi	Support 2.4GHz + 5GHz, IEEE 802.11a/b/g/n/ac wireless card (Intel AX210 module), with roaming switch function
LED Light Bar	RGB LED, UART interface, 5V operation voltage (Option)
Speaker	2 * speaker, rated resistance 7Ω, rated power 0.8W, sensitivity 94dB/10cm
G-Sensor	Automatic screen orientation 3axis
Fan	Smart fan, dimension 45.0 * 45.0 * 5.0mm, working voltage5V, revolution speed 5000RPM, noise 32dB (A)
Rear I/O	Mini USB (host) * 1; Micro SD * 1; 3.5mm audio Jack * 1; Mini HDMI for fast ethernet (10/100) * 1; DC Jack * 1
Pogo Connector	2 * 4pin, with DCIN (Default); 2 * 6pin, with DC IN, LAN (10/100M) (Option)

Battery	Li-ion 16000mAh, 7.4V, 118.4Wh, 14Hrs (Default) Li-ion 12000mAh, 7.4V, 88.8Wh, 10.5Hrs (Option)
Sleep Function	Hall IC switch near pogo pin external magnet action
Power Button	Power button * 1
I/O Cover	Three kinds of optional I/O cover: Rubber cover with logo without button hole (Default) ABS cover with screw hole and button hole (Option) ABS cover with screw hole without button hole (Option)
Operating System	Windows10/Windows11 IoT /pro, 64bits
Certification	FCC/SAR/CE/UKCA
Weight	1.75kg (16000mAh, 7.4V) (Default) 1.62kg (12000mAh, 7.4V) (Option)
Hand Strap	Hand strap for rotating and handle, diameter 60mm stainless steel plate, 95.0 * 95.0mm plastics with 75.0 * 75.0mm VESA hole (Option)
Panel Protector	PET film, 251.9 * 163.4 * 0.125mm (Option)

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reposition or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help. The device has been evaluated to meet general RF exposure conditions.

The device can be used in portable exposure condition without restriction

FCC ID: ZADZ7MGS10109BAX210

Warning: Changes or modifications to this unit not expressly approved by the part responsible for compliance could void the user's authority to operate the equipment.

FCF RF exposure information and statement the SAR limit of USA (FCF is 1.6 W/kg averaged over one gram of tissue. This Gaming tablet had been tested against this SAR limit. This device was tested for typical body-worn operations with the back of the device kept 0mm from the body. To maintain compliance with FCF RF exposure requirements, use accessories that maintain an 0 mm separation distance between the user's body and the back of the device. The use of belt clips, holders and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with FCF RF exposure requirements, and should be avoided.

Guarantee Card

Customer name		Customer TEL NO.	
Sales TEL NO.		Purchase date	
Model			
Customer address			
Sales address			
Maintenance Record			
Date	Failure phenomenon	Solution	Remark

ThinPAD Technology (Shenzhen) CO., LTD

Model: _____

Inspector: _____

Date production: _____

Serial Number: _____

