



Profit from the Eagle Advantage®

Specification Sheet


Short Form Specifications

Eagle Spec-Master® Enclosed Base Worktable, model _____. Top is 14/304 stainless steel, sides and back are heavy gauge stainless steel. (Open Front, Stainless steel Sliding Doors, or Stainless steel Hinged Door) models with 1½" rolled edge on front and rear, sides turned down. Constructed with uni-lok® patented gusset system, with the gussets recessed into the hat channels to reduce lateral movement. 1½" O.D. stainless steel tubular legs with adjustable bullet feet.



enclosed worktable
with sliding doors

Patented uni-lok® System (Patent No. 5,165,349)



Spec-Master® Enclosed Worktables with Flat Top

MODELS:

☐ OB2436SE	☐ CB2436SE	☐ CBH2436SE
☐ OB2448SE	☐ CB2448SE	☐ CBH2448SE
☐ OB2460SE	☐ CB2460SE	☐ CBH2460SE
☐ OB2472SE	☐ CB2472SE	☐ CBH2472SE
☐ OB2484SE	☐ CB2484SE	☐ CBH2484SE
☐ OB2496SE	☐ CB2496SE	☐ CBH2496SE
☐ OB24120SE	☐ CB24120SE	☐ CBH24120SE
☐ OB3036SE	☐ CB3036SE	☐ CBH3036SE
☐ OB3048SE	☐ CB3048SE	☐ CBH3048SE
☐ OB3060SE	☐ CB3060SE	☐ CBH3060SE
☐ OB3072SE	☐ CB3072SE	☐ CBH3072SE
☐ OB3084SE	☐ CB3084SE	☐ CBH3084SE
☐ OB3096SE	☐ CB3096SE	☐ CBH3096SE
☐ OB30120SE	☐ CB30120SE	☐ CBH30120SE

Design and Construction Features

- All-welded design.
- Available with open front, sliding doors, or hinged doors.
- Doors are 20 gauge type 430 stainless steel.
- Top mechanically polished to satin finish.
- Sound-deadened between top and frame.
- 1½" (42mm)-diameter type 304 stainless legs.
- 1" (25mm) stainless steel adjustable bullet feet.
- 1½" (38mm) sanitary rolled rim on front and back with square edge on ends for flush fit.
- Optional fixed center shelf available. To order, add suffix "-CS" to model number. Example: OB2436SE-CS

Options / Accessories

- ☐ Lock (for units with doors)
- ☐ Casters*
- ☐ Overshelf
- ☐ Center shelf
- ☐ Sound deadening

* To order table with 4" (102mm)-diameter casters, add suffix "-CA" (ex: OB3048SE-CA). To order table with 5" (127mm)-diameter casters, add suffix "-CAH" (ex: CB3048SE-CAH).

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA
Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065
www.eaglegrp.com
www.eaglemhc.com

For custom configuration or fabrication needs, contact our SpecFAB® Division.
Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Certifications / Approvals



AutoQuotes



EG10.30 Rev. 11/23

Spec sheets available for viewing, printing or downloading from our online literature library at our websites


Eagle Foodservice Equipment, Eagle MHC, and SpecFAB® are divisions of Eagle Group. ©2023 by the Eagle Group



Profit from the Eagle Advantage®


Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Spec-Master® Enclosed Worktables with Open Front



model #	width in. mm	length in. mm	weight lbs. kg	no. of legs
OB2436SE	24" 610	36" 914	179 81.2	4
OB2448SE	24" 610	48" 1219	238 108.0	4
OB2460SE	24" 610	60" 1524	298 135.2	4
OB2472SE	24" 610	72" 1829	357 161.9	4
OB2484SE	24" 610	84" 2134	417 189.2	6
OB2496SE	24" 610	96" 2438	476 215.9	6
OB24120SE	24" 610	120" 3048	595 269.9	6
OB3036SE	30" 762	36" 914	186 84.4	4
OB3048SE	30" 762	48" 1219	248 112.5	4
OB3060SE	30" 762	60" 1524	309 140.2	4
OB3072SE	30" 762	72" 1829	371 168.3	4
OB3084SE	30" 762	84" 2134	431 195.5	6
OB3096SE	30" 762	96" 2438	494 224.1	6
OB30120SE	30" 762	120" 3048	616 279.4	6


Spec-Master® Enclosed Worktables with Sliding Doors



model #	width in. mm	length in. mm	weight lbs. kg	no. of legs
CB2436SE	24" 610	36" 914	186 84.4	4
CB2448SE	24" 610	48" 1219	249 113.0	4
CB2460SE	24" 610	60" 1524	311 141.1	4
CB2472SE	24" 610	72" 1829	369 167.4	4
CB2484SE*	24" 610	84" 2134	435 197.3	6
CB2496SE*	24" 610	96" 2438	497 225.4	6
CB24120SE*	24" 610	120" 3048	621 281.7	6
CB3036SE	30" 762	36" 914	202 91.6	4
CB3048SE	30" 762	48" 1219	270 122.5	4
CB3060SE	30" 762	60" 1524	336 152.4	4
CB3072SE	30" 762	72" 1829	404 183.3	4
CB3084SE*	30" 762	84" 2134	471 213.7	6
CB3096SE*	30" 762	96" 2438	539 244.5	6
CB30120SE*	30" 762	120" 3048	672 304.8	6

* Note: Worktables 84" (2134mm) and longer have two sets of doors.

Spec-Master® Enclosed Worktables with Hinged Doors



model #	width in. mm	length in. mm	weight lbs. kg	no. of legs
CBH2436SE	24" 610	36" 914	197 89.4	4
CBH2448SE	24" 610	48" 1219	263 119.3	4
CBH2460SE	24" 610	60" 1524	328 148.8	4
CBH2472SE	24" 610	72" 1829	394 178.7	4
CBH2484SE*	24" 610	84" 2134	459 208.2	6
CBH2496SE*	24" 610	96" 2438	525 238.1	6
CBH24120SE*	24" 610	120" 3048	656 297.6	6
CBH3036SE	30" 762	36" 914	207 93.9	4
CBH3048SE	30" 762	48" 1219	276 125.2	4
CBH3060SE	30" 762	60" 1524	344 156.0	4
CBH3072SE	30" 762	72" 1829	413 187.3	4
CBH3084SE*	30" 762	84" 2134	482 218.6	6
CBH3096SE*	30" 762	96" 2438	551 249.9	6
CBH30120SE*	30" 762	120" 3048	689 313.5	6

* Note: Worktables 84" (2134mm) and longer have two sets of doors.

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglehmc.com

Printed in U.S.A.

©2023 by Eagle Group

Rev. 11/23

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.