

CONTACTS

Draper Tools Limited, Hursley Road,
Chandler's Ford, Eastleigh, Hampshire. SO53 1YF. U.K.

Helpline: (023) 8049 4344

Sales Desk: (023) 8049 4333

Internet: drapertools.com

E-mail: sales@drapertools.com

General Enquiries: (023) 8026 6355

Service/Warranty Repair Agent:
For aftersales servicing or warranty repairs, please contact the
Draper Tools Helpline for details of an agent in your local area.


YOUR DRAPER STOCKIST

PJMC1118

©Published by Draper Tools Limited.
No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means,
electronic, mechanical photocopying, recording or otherwise without prior permission in writing from Draper Tools Ltd.

DRAPER
Expert

FIBREGLASS
STEP LADDERS
90409, 90417, 90420.



EN131 PROFESSIONAL

These instructions accompanying the product are the original instructions. This document is part of the product, keep it for the life of the product passing it on to any subsequent holder of the product. Read all these instructions before assembling, operating or maintaining this product.
This manual has been compiled by Draper Tools describing the purpose for which the product has been designed, and contains all the necessary information to ensure its correct and safe use. By following all the general safety instructions contained in this manual, it will ensure both product and operator safety, together with longer life of the product itself.
All photographs and drawings in this manual are supplied by Draper Tools to help illustrate the operation of the product.
Whilst every effort has been made to ensure the accuracy of information contained in this manual, the Draper Tools policy of continuous improvement determines the right to make modifications without prior warning.

1. TITLE PAGE

1.1 INTRODUCTION:

USER MANUAL FOR: FIBREGLASS STEP LADDERS
Stock No's: 90409, 90417, 90420.
Part No's: FGL3A, FGL5A, FGL7A.

1.2 REVISIONS:

Date first published November 2018.

As our user manuals are continually updated, users should make sure that they use the very latest version.

Downloads are available from: <http://drapertools.com/manuals>

Draper Tools Limited
Hursley Road
Chandler's Ford
Eastleigh
Hampshire
SO53 1YF
UK

Website: drapertools.com
Product Helpline: +44 (0) 23 8049 4344
General Fax: +44 (0) 23 8026 0784

1.3 UNDERSTANDING THIS MANUALS SAFETY CONTENT:

WARNING! – Information that draws attention to the risk of injury or death.

CAUTION! – Information that draws attention to the risk of damage to the product or surroundings.

1.4 COPYRIGHT © NOTICE:

Copyright © Draper Tools Limited.
Permission is granted to reproduce this publication for personal and educational use only. Commercial copying, redistribution, hiring or lending is prohibited.
No part of this publication may be stored in a retrieval system or transmitted in any other form or means without written permission from Draper Tools Limited.

In all cases this copyright notice must remain intact.

10. DISPOSAL

10.1 DISPOSAL

– At the end of the ladder's working life, or when it can no longer be repaired, ensure that it is disposed of according to national regulations.
– Contact your local authority for details of collection schemes in your area.
In all circumstances:
• Do not abandon in the environment.

9. EXPLANATION OF SYMBOLS



Warning, fall from the ladder.



Refer to instruction manual/booklet



Inspect the ladder after delivery. Before every use visually check the ladder is not damaged and is safe to use. Do not use a damaged ladder.



Maximum total load



Do not use the ladder on a uneven or infirm base.



Do not overreach.




Do not erect ladder on contaminated ground.




Maximum number of users.



Do not ascend or descend unless you are facing the ladder.



Warning, electricity hazard identify any electrical risks in the work area, such as overhead lines or other exposed electrical equipment and do not use the ladder where electrical risks occur.



Do not stand on the top two steps/rungs of a standing ladder without a platform and a hand/knee rail.



Keep a secure grip on the ladder when ascending and descending. Maintain a handhold whilst working from a ladder or take additional safety precautions if you cannot.



Avoid work that imposes a sideways load on ladders, such as side-on drilling through solid materials.



Do not carry equipment which is heavy or difficult to handle while using a ladder.



Do not wear unsuitable footwear when climbing a ladder.



Do not use the ladder if you are not fit enough. Certain medical conditions or medication, alcohol or drug abuse could make ladder use unsafe.




Do not use the ladder as a bridge.




Ladder for professional use.




Do not step off the side of standing ladder onto another surface.



Open the ladder fully before use.



Use the ladder with restraint devices engaged only.



Standing ladders shall not be used as a leaning ladder unless it is designed to do so.

3. INTRODUCTION

3.1 SCOPE

This ladder is an A-frame step ladder of between 3-7 rungs plus a plastic top cap. It is used to allow safe temporary access to areas outside the normal reach of the user.
Any application other than that it was intended for, is considered misuse.

3.2 SPECIFICATION

Stock No.....	90409	90417	90420
Part No.....	FGL3A	FGL5A	FGL7A
Number of rungs.....	3	5	7
Closed height.....	1.2m	1.8m	2.4m
Open height.....	1.06m	1.615m	2.17m
Spread.....	0.881m	1.275m	1.669m
Max. standing height.....	0.26m	0.82m	1.38m
Weight.....	6.1kg	8.kg	11.6kg
Max. Load.....	150kg	150kg	150kg

(EN131 Professional)

3.3 HANDLING & STORAGE

Take care when handling the ladder.
Store in a dry location, out of the reach of children.

8. CARE & MAINTENANCE

NOTE: Repairs and maintenance shall be carried out by a competent person and in accordance with the manufacturers instructions.

8.1 INSPECTION

For regular inspection, the following items shall be taken into account:
– check that the stiles/legs (uprights) are not bent, bowed, twisted, dented, cracked, corroded or rotten;
– check that the stiles/legs around the fixing points for other components are in good condition;
– check that fixings (usually rivets, screws or bolts) are not missing, loose, or corroded;
– check that rungs/steps are not missing, loose, excessively worn, corroded or damaged;
– check that the hinges between front and rear sections are not damaged, loose or corroded;
– check that the locking stays horizontal, back rails and corner braces are not missing, bent, loose, corroded or damaged;
– check that the rung hooks are not missing, damaged, loose or corroded and engage properly on the rungs;
– check that guide brackets are not missing, damaged, loose or corroded and engage properly on the mating stile;
– check that ladder feet / end caps are not missing, loose, excessively worn, corroded or damaged;
– check that the entire ladder is free from contaminants (e.g. dirt, mud, paint, oil or grease);
– check that locking catches (if fitted) are not damaged or corroded and function correctly;
– check that the platform (if fitted) has no missing parts or fixings and is not damaged or corroded.
If any of the above checks cannot be fully satisfied, you should NOT use the ladder.

5. TECHNICAL DESCRIPTION

5.1 IDENTIFICATION

① Rubber feet.

② Top plate.

③ Rung.

④ Lock bar.



Shown stock No.90409

4. HEALTH AND SAFETY INFORMATION

4.1 WARNING

Failure to adhere to the warnings and instructions contained in this manual and on the product could result in serious injury or death.
The ladder is designed and intended for professional use.
This ladder is NOT a toy. Children should be supervised at all times to ensure they do not use or play with the ladder or its components.
Only use the ladder as described in these instructions. Any other use is deemed improper and may result in damage to property, personal injury or death.

7. INSTRUCTIONS FOR USE

7.1 REASONS FOR ACCIDENTS

– Is the ladder stored away from areas where its condition could deteriorate more rapidly (e.g. dampness, excessive heat, in direct sunlight or exposed to the elements)?
– Is the ladder stored in a position which helps it to remain straight (e.g. hung by the stiles on proper ladder brackets or laid on a flat clutter free surface)?
– Is the ladder stored where it cannot be damaged by vehicles, heavy objects, or contaminants?
– Is the ladder stored where it cannot cause a trip hazard or an obstruction?
– If the ladder is permanently positioned (e.g. on scaffolding), is it secured against unauthorized climbing (e.g. by children)?

7.2 BEFORE USE

– Use non-conductive ladders for unavoidable live electrical work.
– Do not modify the ladder design.
– Do not move a ladder while standing on it.

7.3 POSITIONING AND ERECTING THE LADDER

– Use non-conductive ladders for unavoidable live electrical work.
– Do not move a ladder while standing on it.

7.4 USING THE LADDER

– Use non-conductive ladders for unavoidable live electrical work.
– Do not move a ladder while standing on it.

7.5 OPERATION

Open ladder and lock by pressing down on lock bars. Do not climb unless locked. Ensure ladder is on safe, stable and level ground during use.

6. UNPACKING AND CHECKING

6.1 PACKAGING

Carefully remove the product from the packaging and examine it for any sign of damage that may have happened during shipping. If any part is damaged or missing, please contact the Draper Help Line (the telephone number appears on the Title page) and do not attempt to use the product.

Warning!

• Some of the packaging materials used may be harmful to children. Do not leave any of these materials in the reach of children.
• If any of the packaging is to be thrown away, make sure they are disposed of correctly, according to local regulations.

7. INSTRUCTIONS FOR USE

7.1 BEFORE USE

a) Ensure that you are fit enough to use a ladder. Certain medical conditions or medication, alcohol or drug abuse could make ladder use unsafe;
b) When transporting ladders on roof bars or in a truck, ensure they are suitably placed to prevent damage;
c) Inspect the ladder after delivery and before first use to confirm condition and operation of all parts;
d) Visually check the ladder is not damaged and is safe to use at the start of each working day when the ladder is to be used;
e) Periodic inspection is required;
f) Ensure the ladder is suitable for the task;
g) Do not use a damaged ladder;
h) Remove any contamination from the ladder, such as wet paint, mud, oil or snow;
i) Before using a ladder at work a risk assessment should be carried out respecting the legislation in the country of use;

7.2 POSITIONING AND ERECTING THE LADDER

a) Ladder shall be erected at the correct position, such as the correct angle for a leaning ladder (angle of inclination approximately 1:4) with the rungs or treads level and complete opening of a standing ladder;
b) Locking devices shall be fully secured before use;
c) Ladder shall be on an even, level and unmovable base;
d) Leaning ladder should lean against a flat non-fragile surface and should be secured before use, e.g. tied or use of a suitable stability device;
e) Ladder shall never be repositioned from above;
f) When positioning the ladder take into account risk of collision with the ladder e.g. from pedestrians, vehicles or doors. Secure doors (not fire exits) and windows where possible in the work area;
g) Identify any electrical risks in the work area, such as overhead lines or other exposed electrical equipment;
h) Ladder shall be stood on its feet, not the rungs or steps;
i) Ladders shall not be positioned on slippery surfaces (such as ice, shiny surfaces or significantly contaminated solid surfaces) unless additional effective measures are taken to prevent the ladder slipping or ensuring contaminated surfaces are sufficiently clean.

7. INSTRUCTIONS FOR USE

7.1 REASONS FOR ACCIDENTS

The following list of hazards and examples of their causes, which is not exhaustive, are common reasons for accidents encountered when using ladders and are the basis on which the information in this standard has been developed.
a) Loss of stability:
1) Incorrect positioning of the ladder (such as incorrect angle for leaning ladder or not fully opening a standing ladder);
2) Slide outwards at the bottom (such as bottom of the ladders sliding away from the wall);
3) Side slip, falling sideways and top flip (such as overreaching or fragile top contact surface);
4) Condition of the ladder (such as missing anti-slip feet);
5) Stepping off an unsecured ladder at height;
6) Ground conditions (such as unstable soft ground, sloping ground, slippery surfaces or contaminated solid surfaces);
7) Adverse weather conditions (such as windy conditions);
8) Collision with the ladder (such as vehicle or door);
9) Incorrect choice of ladder (such as too short, unsuitable task).
b) From handling:
1) Transferring the ladder to the work position;
2) Erecting and dismantling the ladder;
3) Carrying items up the ladder.
c) Slip, trip and fall of user:
1) Inappropriate footwear;
2) Contaminated rungs or steps;
3) Unsafe user practices (such as climbing 2 rungs at a time, sliding down stiles).
d) Structural failure of the ladder:
1) Condition of the ladder (such as damaged stiles, wear UV degradation of plastic parts);
2) Overloading the ladder.
e) Unintended use:
1) Electrical hazards:
1) Unavoidable live working (e.g.: fault finding);
2) Positioning ladders too close to live electrical equipment (such as overhead power lines);
3) Ladders damaging electrical equipment (such as covers or protective insulation);
4) Incorrect selection of type of ladder for electrical work.