1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	**FLUID FOR LINE LEVEL**
1.2	Chemical Name:	Low Boiling Point Naphtha
1.3	Synonyms:	P/N 67765
1.4	Trade Names:	Pittsburgh
1.5	Product Uses & Restrictions:	Sight-Glass
1.6	Distributor's Name:	Harbor Freight Tools USA, Inc.
1.7	Distributor's Address:	26541 Agoura Road, Calabasas, CA 91302 USA
1.8	Emergency Phone:	**CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 676687)**
1.9	Business Phone / Fax:	+1 (805) 388-1000

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION.

Classification: Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aq. Chronic 2.

Hazard Statements (H): H224 – Extremely flammable liquid and vapor. H304 – May be fatal if swallowed and enters airways. H319 – Causes serious eye irritation.

Precautionary Statements (P): P201 – Obtain special instruction before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). P305+P351+P338 – IF IN EYES – Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P370+P378 – In case of fire: use CO_2, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					ACGIH		NOHSC			OSHA			
					ppm		ppm			ppm			
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	OTHER
LOW BOILING POINT NAPHTHA	8006-61-9	LX3300000	232-349-1	60-100	100	NA	NF	790	NF	200	NA	2000	MIST
	Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aq. Chronic 2; H224, H304, H315, H336, H411												

4. FIRST AID MEASURES

4.1 First Aid:

Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.

Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

Skin: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

Inhalation: Remove victim to fresh air at once.

4. FIRST AID MEASURES – cont'd

4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. Eyes: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue may occur.
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.
4.5	Chronic Health Effects:	The material may accentuate any pre-existing dermatitis condition.
4.6	Target Organs:	Eyes, Skin, Respiratory System, Central Nervous System, Liver, Kidneys
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARDS	0
PROTECTIVE EQUIPMENT	X

EYES	SKIN	LUNGS

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	**DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR!** Keep away from heat/ sparks/ open flame/ hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge.
5.2	Extinguishing Methods:	CO_2, Halon (if permitted), Dry Chemical, Foam, as authorized.
5.3	Firefighting Procedures:	This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3[Y]E. Hazard Identification Number: 33



6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Storage temperature: 32-120 ºF (0-49 ºC). Take precautionary measures against static discharge. Store away from incompatible materials (see Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

			ACGIH		NOHSC			OSHA			OTHER
8.1	Exposure Limits: ppm (mg/m^3)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		LOW BOILING POINT NAPHTHA	100	NA	NF	790	NF	200	NA	2000	MIST
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans), to keep exposure below the airborne exposure limits. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia.									
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.									
8.5	Hand Protection:	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the EU member states.									
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. Wear appropriate protective clothing to prevent skin contact, (boots, lab coat, apron, coveralls) as needed. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Transparent liquid (may be yellow-green)
9.2	Odor:	Penetrating hydrocarbon odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	> 60 ºC (>140 ºF)
9.7	Flashpoint:	< 0 ºC (< 32 ºF)
9.8	Upper/Lower Flammability Limits:	LEL: 0.7% / UEL 7.0%
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA
9.11	Relative Density:	NA
9.12	Solubility:	Insoluble in water
9.13	Partition Coefficient (log P_{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability:	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion:	YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Low Boiling Point Naphtha: LD_{50} (oral, rat): 5,000 mg/kg.					
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.					
11.4	Chronic Toxicity:	The material may accentuate any pre-existing dermatitis condition.					
11.5	Suspected Carcinogen:	Low Boiling Point Naphtha: IARC Group 2B – possibly carcinogenic to humans.					

11. TOXICOLOGICAL INFORMATION – cont'd

11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
11.8	Biological Exposure Indices:	NE
11.9	Physician Recommendations:	Treat symptomatically.

12. ECOLOGICAL INFORMATION


12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	NA

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR)*:	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L); or UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1993, LIQUIDOS, INFLAMABLES, N.E.P. (NAFTA), 3, II (CANT. LTDA., IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1993, FLAMMABLE LIQUIDS, N.O.S. (NAPHTHA), 3, II (LTD QTY, IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.
15.4	CERCLA Reportable Quantity (RQ):	NA
15.5	Other Federal Requirements:	None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors.
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects). 
15.7	State Regulatory Information:	Low Boiling Point Naphtha (as Natural Gasoline) is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). **WARNING**! This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.

15. REGULATORY INFORMATION – cont'd

15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Low Boiling Point Naphtha: Highly Flammable, Harmful (F+, Xn). Risk Phrases (R): R11-36/37/38-65 – Highly flammable. Irritating to eyes, skin and respiratory system. Harmful: may cause lung damage if swallowed. Safety Phrases (S): (2-)9-16-26-46 – Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately (show the label where possible).



16. OTHER INFORMATION

16.1	Other Information:	**DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION.** Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). IF IN EYES – Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: use CO_2, Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. Store locked up. **KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.** **WARNING**! This product contains a substance(s) known to the State of California to cause cancer, birth defects or other reproductive harm.
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Harbor Freight Tools USA, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for:	**Harbor Freight Tools USA, Inc.** 26541 Agoura Road Calabasas, CA 91302 USA Tel: +1 (805) 388-1000 http://www.harborfreight.com
16.5	Prepared by:	**ShipMate, Inc.** P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		**G**	
B		**H**	
C		**I**	
D		**J**	
E		**K**	
F		**X**	**Consult your supervisor or SOPs for special handling directions.**

Safety Glasses | **Splash Goggles** | **Face Shield & Protective Eyewear** | **Gloves**

Boots | **Synthetic Apron** | **Protective Clothing & Full Suit** | **Dust Respirator**

Full Face Respirator | **Dust & Vapor Half-Mask Respirator** | **Full Face Respirator** | **Airline Hood/Mask or SCBA**

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD_{50}	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC_{50}	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD_{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD_{lo}, LD_{lo}, & LD_o or TC, TC_o, LC_{lo}, & LC_o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{OW} or log K_{OC}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

							
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

							
C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

								
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ-ment