




Kasa Smart Wi-Fi Light Switch, Dimmer

2-Gang, Single Pole

HS220-2



Highlights


Brightness Control

Control the brightness of your lights to set the perfect ambiance for any activity.



Voice Control


Use simple voice commands with Alexa and Google Assistant to conveniently control the lights without leaving your spot.



Highlights


Fade On/Off

Smoothly illuminate or dim your lamps without sudden eye-irritating brightness or darkness.



Set Schedules

Program your connected lights to adjust their brightness or turn on/off based on your daily routine and preferences.



Features

- **Sleek 2-Gang Design**

Skip the hassle of finding a matching wall plate. Just snap on the included wall plate for a seamless fit. The screwless design adds a more streamlined, sophisticated touch to your interior.

- **Remote Control**

Control your connected lights from anywhere, anytime via the free Kasa Smart app.

- **Away Mode**

Set your smart light switch to turn connected fixtures on and off at random intervals to give the appearance you're home even while you're away.

- **UL Certified**

Housed with V-0 (UL94) flame-retardant material, the smart dimmer switch is UL listed for safety use.

- **Group & Scene**

Group your smart switch with other smart devices to control them all at once. Set custom scenes to match any occasion like waking up.

- **No Hub Required**

Easily connect directly to your secured 2.4GHz home Wi-Fi network.

- **Led Indicator**

With an illuminating LED indicator, you'll always be able to find your smart dimmer switch even when it's dark.



Specifications

Electrical

- Rating: 120V~ 60Hz
- Max Load (Each): 300W INC/HAL, 150W LED
- In-Wall Depth: 1.35 in (34.2 mm)
- Wall Plate Dimensions: 5.14 × 5.07 in (130.7 × 128.7 mm)
- Dimming Type*: Leading Edge Dimming / TRIAC Phase Cut

*We recommend contacting your bulb's customer support to verify its compatible dimming options.

- Neutral wire required
- Standard wall box (at least 2 inches deep)
- Single pole switch. Not compatible with 3-way (multi-location) wiring.

Requirements

- IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
- Kasa Smart app and account

Please do not use in damp environments or outdoors.

General

- Indoor Use Only
- Buttons: Switch Button, Restart Button, Reset Button, Brightness Up/Down Buttons
- Operating Temperature: 0 °C ~ 40 °C (32°F ~ 104°F)
- Operating Humidity: 10%~90%RH, Non-condensing
- Certifications: FCC, IC, UL, RoHS

Package Contents

- 2× Smart Wi-Fi Dimmer Switches
- 1× 2-Gang Wall Plate
- 4× Screws
- 4× Wire Nuts
- Wire Labels
- Mounting Template
- Quick Start Guide

