

HYCHIKA®

Instruction Manual

Hole Saw Kit HS1C7C

- 13PCS Saw Blade :
3/4 "(19mm), 7/8" (22mm), 1 - 1/8" (28mm),
1 - 1/4" (32mm), 1 - 1/2" (38mm), 1 - 3/4" (44mm),
2" (51 mm), 2- 11/16 " (68mm), 3" (76mm),
3- 1/2" (89mm), 4" (102mm), 5" (127mm),
6" (152mm),
- 2pcs Mandrels ● 1 pc Installation plate
- 1pc Hex key ● 1pc package Box

- Use Hole saws with care
- Max cutting depth:25mm
- suitable for materials:timber, plastic & plaster only
- Not suitable for cutting metal & fibre cement sheeting
- Do not over tighten grub screws
- Remove debris from teeth for cutting efficiency

Recommended operating speed(RPM)

Hole saw diameter	RPM
19-38MM	750
44-64MM	550
76-89MM	450
127- 1 52MM	350

Installation method

See the picture on the right for specific installation methods.



Precautions for use

1. The hole saw needs to be perpendicular to the working surface when working.
Note: Drilling cannot be performed at an angle, as this may cause damage to the drill bit



WARNING FOR YOUR SAFETY EYE GOGGLES ARE RECOMMENDED TO BE WORN DURING USE .

Note: Larger hole saw are recommended touse at slower speed to maxi- mise life.Ensure pilot are sharpened regularly.