

尺寸 : 152x96 mm

材质：105g 铜版纸

工艺：双面黑白印刷

折纸，英文面照上，顺序从左到右，注意反面时也是一样。

Smart Siren Alarm

— Siren Alarm —
— Manual —



Please pay special attention! The positive and negative poles of the battery are in the correct direction! After installing the battery, snap the backcover into the main body and push it upwards to secure the back cover.

CE RoHS V

Installation method

Insert the isolated double-sided adhesive film on the back cover of the product and then affix it to the object that needs to be installed (ensure the surface of the object is clean and dry and avoid mounting) on an object that constantly produces vibration (if the sensor is not a siren function, it can be placed and installed as desired).

Function description of vibration detection alarm (only applicable for product ZO-282 with vibration detection function)

- After the device is powered on, it will enter the vibration detection function only after 38 seconds and two beeps. The indicator light will flash once every 5 seconds, indicating that the device has entered the armed mode.
- In the app, you can set the device status to armed/disarmed. Only when in armed mode, the siren will sound when the device vibrates.
- After the device is armed, the indicator light will flash every 5 seconds.
- This device features real-time online functionality, allowing users to remotely issue commands to the sensor in real time, such as setting the alarm to eliminate the alarm sound, and setting up automatic scenarios for linking.
- After the equipment vibrates, an alarm will be triggered. The factory default alarm duration is 60 seconds, which can be adjusted on the APP.
- Clicking the "SET" button can switch the alarm sound to "Siren" or "Music".

Function description of sound and light alarm (only applicable to sound and light alarm product ZO-292S)

- The device features real-time online functionality, allowing users to set up automated scenarios for interconnection, such as sounding an alarm or ringing a doorbell.
- The factory default alarm sound sounding time is 60 seconds, which can be set on the APP.
- Click the "SET" button to adjust the alarm volume, with options including "highest", "medium", "low", and "mute".

Product Name	Smart Siren Alarm
Operating Current	<200mA
Battery Type	Li-ion 3.6V 2000mAh
Standby Current	<15mA
Standby Time	>12 Months
Built-in Siren	>110dB
Operating Temperature	-10°C ~ 45°C
Operating Humidity	20%~95% RH
Product Size	70x30x40mm
Vibration Detection	1~50s (only for vibration alarm)

[illegible]

FCC Caution.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

* RF warning for Portable device:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.