
TVGO NEO

User Manual



SLAM Solution | February. 2026

Table of Content

1 Reading Tips	4
1.1 Symbols	4
1.2 Safety Guidelines	4
1.2.1 Laser Safety Class	4
1.2.2 Device Drop	5
1.2.3 Power Supply	5
1.2.4 Transportation and Vibration	5
1.2.5 Battery Safety	5
1.2.6 Chemistry	5
1.2.7 Surface High Temperature	5
1.2.8 Use of Equipment	5
2 Introduction	7
2.1 Check List	7
2.2 Equipment Specifications, Dimensions and Interface	9
2.3 Product Parameters	10
3 Product Usage	13
3.1 Work	13
3.1.1 Battery Charge	13
3.1.2 Equipment Installation	14
3.1.3 Mobile Phone Bracket Installation	14
3.1.4 Software	15
3.2 Data Acquisition	16
3.2.1 Equipment Start-up	16
3.2.2 Device Connection	17
3.2.3 Device Diagnostics	17
3.2.4 Project Management	18
3.2.5 Log Upload	18
3.2.6 Infrastructure	19
3.2.7 RTK Settings	19
3.2.8 Other Settings	20

3.2.9 Start Collecting	21
3.2.10 One-click Collection	24
4 Collection Guide	26
4.1 Route Planning	26
4.2 Loop Requirement	26
4.3 Precautions for Data Acquisition	26
5 Data Processing	28
5.1 Data	28
5.1.1 Data Copying	28
5.1.2 File Structure	28
5.1.3 Data Cleaning	29
5.2 Software Installation	29
5.2.1 Install	29
5.2.2 Software Registration	30
5.3 Data Resolution	31
5.3.1 New Construction	31
5.3.2 Coordinate System Setup	32
5.3.3 Real-time Point Cloud Loading	34
5.3.4 One-click Refinement	35
5.3.5 Results Browsing	44
5.4 Point Cloud Display	44
5.5 Export Results	45
6 Frequently Asked Problems and Solutions	46
6.1 TVGO NEO Host	46
6.2 TrueView Go	46
7 Daily Use and Precautions	47
7.1 Use	47
7.2 Daily Service Specification	47
7.3 Equipment Transportation	48
7.4 Equipment Storage	48

1 Reading Tips

1.1 Symbols

Forbid 

Warning 

Important note 

Operate & Using tips 

1.2 Safety Guidelines

1.2.1 Laser Safety Class


Complies with FDA performance standards for laser products except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019.

Laser safety levels are classified according to IEC 60825-1: 2014.

Caution – Use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.

The laser module information is as follows :

Maximum single pulse energy:	$1.29 * 10^{-6} \text{J}$
Pulse width:	2ms & 500ns
Repetition frequency:	10Hz & 9kHz



1.2.2 Device Drop

This product contains precision electronic components.

- Dropping, crushing, puncturing, or improper handling may cause permanent damage.
- If the device is dropped, stop using it immediately and contact after-sales support for assistance.

1.2.3 Power Supply

- Ensure the power interface is dry and free of debris before powering on.
- Only use power cables and adapters provided or approved by TrueView.
- Do not use damaged power cables or adapters that do not meet the specified power requirements.

1.2.4 Transportation and Vibration

- Avoid strong vibration and mechanical shock to prevent damage to the device.
- Mechanical shock or vibration exceeding the allowable range may damage the product.
- TrueView is not responsible for equipment damage caused by improper logistics handling during transportation.

For detailed shock and vibration specifications, please contact TrueView technical support.

1.2.5 Battery Safety

- Do not immerse the battery in water. Store it in a cool, dry place when not in use.
- Keep the battery away from heat sources during both use and storage.
- Avoid short circuits by keeping battery terminals away from metal objects.
- Do not tap, drop, or step on the battery.
- Do not weld or puncture the battery with sharp objects.
- If the battery will not be used for an extended period, maintain its charge level between 30% and 50%. Fully charge and discharge the battery at least once every three months.

After around 500 charge cycles, battery capacity may decrease to approximately 80% of the original capacity.

1.2.6 Chemistry

Do not expose the product to corrosive or highly reactive chemicals (liquids or gases), including but not limited to strong acids, strong bases, esters, or ethers. Such exposure may cause damage, including the loss of waterproof protection.

1.2.7 Surface High Temperature

During operation and for a period after use, the device surface may become hot.

- Avoid direct skin contact with the product shell to prevent burns.
- Keep flammable materials away from the device to reduce the risk of fire.

1.2.8 Use of Equipment

Use and maintain the device in accordance with this user manual. Damage, reduced service life, or malfunction resulting from improper use, improper maintenance, or unauthorized disassembly is not covered by warranty. All related repair and maintenance services will be charged according to standard service fees.

2 Introduction

The TVGO NEO is a tool-level entry-level handheld SLAM 3D scanning product launched by TrueView, delivering uncompromising performance. It adopts deep integration of high-precision inertial navigation and SLAM technology, incorporating a high-frequency ultra-wide-angle LiDAR for full-grid online scanning details and a 48MP high-definition camera for pixel-level reproduction of scanned scenes. The device features fully open hardware interfaces and SDKs, and together with CoCloud, builds a cloud-integrated data processing workflow. Focused on full-scenario adaptability with a minimalist operation process, the TVGO NEO is primarily used in fields such as architectural surveying, interior design, decoration and renovation, and underground space measurement. It provides a cost-effective 3D data acquisition entry-level solution that reduces costs and increases efficiency.

2.1 Check List

 **Note:** Please refer to the actual delivery list.


TVGO NEO Surveying System configuration list is shown below:

N	Description	Pcs	Type
1	TVGO NEO unit	1	Standard
2	Smart Handle	1	Standard
3	Phone Holder	1	Standard
4	Laser Head Protective Cover	1	Standard
5	Laser Head Lens Cleaning Cloth	1	Standard
6	Power Adapter	1	Standard
7	Data Cable	1	Standard
8	Quick Start Guide	1	Standard
9	1/4 to 5/8 nut converter	1	Optional
10	Tripod	1	Optional


2.2 Equipment Specifications, Dimensions and Interface

The weight of the equipment is about 1.2 kg.

The length, width and height (118 × 90 × 304 mm) are as follows:



Interfaces and Indicators



- | | |
|-----------------------------|-------------------------------|
| ① LiDAR | ⑥ Data transmission interface |
| ② RTK antenna | ⑦ Handle battery button |
| ③ Camera | ⑧ Charging port |
| ④ Unit status indicator | ⑨ Function button |
| ⑤ Handset bracket interface | ⑩ Handle battery indicator |

2.3 Product Parameters

System parameter	Absolute accuracy	Horizontal: < 3cm RMS ① Vertical: < 3cm RMS ①
	Relative accuracy	<1cm②

Laser parameters	Repetition accuracy	<2cm②
	Power supply	Battery Handle
	Battery capacity	46.08Wh
	Single cell operating time	About 150 minutes ③
	Power consumption	16W
	Waterproof and dustproof grade	IP64④
	Storage capacity	512G
	Operating temperature	-20~50°C
	Weight	1.2kg (including handle battery)
	Field of view	360°*189°
	Laser safety class	Class1
	Ranging	40m (10% reflectivity)
	Point frequency	1152000 points/sec
	Number of laser channels	64
	Wavelength	905nm
	Echo	2
Position and pose system	Satellite system	GPS: L1, L2, L5 GLONASS: L1, L2, Galileo: E1, E5a, E5b BeiDou: B1,B2,B3 QZSS: L1C/A, L1C, L2C, L5, L6
IMU	UPDATE	500Hz
	Gyroscope bias instability	0.5°/hr

	Gyroscope random walk	0.01°/√hr
	Accelerometer bias instability	10ug
	Accelerometer random walk	0.017m/s/√hr
Camera	Quantity	2
	Resolution	4800w
	Sensor size	1/2 in.
	Field of view	340° (H) *360° (V)

①② Measured at the TrueView standard test site. Deviations may occur in certain scenarios.

③ Measured at room temperature (25 °C) with the equipment at rest.

④It offers splash-proof, waterproof, and dustproof protection. This protection performance has been tested and verified in a standard laboratory environment. According to the IEC 60529 standard, the protection level is rated IP64.


3 Product Usage

3.1 Work

3.1.1 Battery Charge

Use the standard power adapter to connect the charging cable to the handle battery.

- It takes approximately 2 hours to charge the battery power from 0% to 100%.
- Do not connect the charging cable to the Type-C interface of the host, and turn off the phone to charge.




The device indicator light shows the remaining battery power of the handle, please refer to the table below for details.

indicator lamp	state	Device power
	One-cell indicator flashing	0-10%
	One-cell indicator lamp always on	10%-20%
	One-cell indicator flashing, one-cell indicator lamp always on	20%-30%
	Two-compartment indicator lamp always on	30%-40%
	Two-compartment indicator lamp always on, one-cell indicator flashing	40%-55%
	Three-compartment indicator lamp always on	55%-70%
	Three-compartment indicator lamp always on, one-cell indicator flashing	70%-85%
	Four-compartment indicator lamp always on	85%-100%

3.1.2 Equipment Installation


- Release the handle latch,
- Insert the battery handle into the bottom groove of the main unit.
- Ensure the battery is securely installed, then lock the handle latch.

Caution: Ensure the handle latch is locked, otherwise it may cause poor battery or device drop.



3.1.3 Mobile Phone Bracket Installation

- Align the bottom of the mobile phone mount with the mounting interface on the back of the main unit.
- Tighten the mounting knob to secure the bracket.
- After the installation is completed, the angle of the bracket can be freely adjusted.




3.1.4 Software

The TVGO NEO data acquisition software is TrueView Go, a comprehensive application control software . It covers four major modules: airborne, vehicle-mounted, handheld, and Lidar setting tools, enabling device control and data acquisition functions. TrueView Go provides a full 3D display of routes and terrain, presenting complex work sites to users more intuitively.

3.2 Data Acquisition

3.2.1 Equipment Start-up




- After the handle battery is installed, short-press and long-press the buttons under the handle for 2 seconds.
- When the power indicator lights turn on in turn and the host indicator light is solid green, the device is turned on.

Main Unit Indicator Status

Indicator Light Status	Meaning
Green Light Steady On	Device Powered On
Blue Light Running Light	Device Self-Checking
Blue Light Steady On	Device Self-Check Completed, Ready
Green Light Fast Blinking	Device Initializing
Blue Light Slow Breathing	Device Collecting Data
Green Light Slow Blinking	Data Saving
Yellow Light Breathing	Abnormal During Data Collection
Red & Green Lights Alternately Blinking	Firmware Upgrading
Red Light Steady On	Device Fault

3.2.2 Device Connection

- Open the TrueView Go software and select SLAM job, select the device WIFI name starting with SLAM-xxxx on the device connection interface and connect, no password is required.




After connection:

- Check device battery level and remaining storage.
- Check firmware and software versions.
- Confirm device authorization status. If authorization has expired, contact TrueView technical support.


3.2.3 Device Diagnostics

- Click device diagnostics to view the status of various sensors of the current device. If there is any abnormality, restart the device and try to recover. If the restart cannot be resolved, contact the after-sales personnel of TrueView.




3.2.4 Project Management

- Click on the project management to view historical collected project information, including project name, real-time point cloud thumbnails, creation time, collection time, collection mileage, etc.
- Click Manage to manually delete historical projects, then the raw data in device will be synchronized delete too.



3.2.5 Log Upload


- If you encounter problems during the use of the device, you can upload the log for analysis. When the device is connected, click the  upper right corner of the software to select Log Management and click Package Log.
- Select the corresponding date and confirm. The software will automatically package the current device log.
- After clicking Upload, you can Contact TrueView after-sales personnel to download.



3.2.6 Infrastructure

After connecting the device, click 'Start Capture' to enter the collection interface, click the setting button in the upper right corner of the software to enter the basic setting interface.

- Turn on the 'Colored point clouds', it will use camera to coloring the point clouds in real time during the data collection process.
- Turn on the 'Use camera', and the camera will take photos when the device collecting data, which can be used to coloring point clouds, build mesh models, etc. The camera will not work if disable this function.
- The low battery reminder percentage can be set. When the set threshold is reached, TrueView Go will actively remind that the battery is too low, please charge in time.
- Turn on the broadcast, and the software will broadcast the status information of the device in real time during the use.




3.2.7 RTK Settings

- After connected, enter the collection interface, click the setting button in the upper right corner, enter the RTK setting interface, open the CORS account type, enter the

corresponding server address, port, user name and password, obtain the source list, and click Connect.

- The types of CORS accounts currently supported are: CORS, APIS.



Note: Ensure the device is under CORS coverage and the mobile phone has internet access.

3.2.8 Other Settings

The main interface of the software can display device status information in real time. The specific information types and explanations are as follows:



Displays memory used and remaining on device



Indicates the connection status of the phone and device



Indicates the satellites search status and number




Indicates the remaining power of the device




Indicates the remaining battery of the phone



Point clouds of different elevation ranges can be displayed with this setting



Point clouds can be restored to top view state with one click



Can display/hide real-time point cloud information with one click



Different point cloud renderings, currently supporting elevation rendering, intensity rendering, mixed rendering and color rendering




You can clear the real-time point cloud of the TrueView Go interface with one click, this operation will not delete the collected data inside the device



The current warning and error information of the device will be displayed, please deal with it according to the displayed information, if it cannot be resolved, please contact TrueView after-sales service

3.2.9 Start Collecting


① **Create a project:** Enter the acquisition interface, click the orange button on the left side of the screen to create a new project. The default project name is the collection time and the last four digits of the device SN. Manual modification of the project name is supported.



② **Equipment initialization:** After the project is created, it needs to be initialized. Refer to the following initialization precautions:


- Once the equipment stabilizes, the countdown disappears and initialization is complete—no need to place it on the ground.
- During initialization, point the device toward feature-rich objects such as buildings, irregular rocks, etc., and avoid open or featureless areas.
- The laser protective cover must be removed during initialization. Avoid pointing the device at moving objects or manually blocking the laser head.
- Try to avoid highly reflective objects such as glass or mirrors during initialization to

reduce noise.



③ **Data collection:** Once initialization is complete, data collection can begin according to the pre-planned walking route. During the process, the TrueView Go interface displays the collection trajectory and real-time point cloud information. Use one finger to drag and rotate the point cloud, and two fingers to drag and translate it. Throughout the collection, pay close attention to the real-time point cloud display to ensure complete coverage of the target area without any missing data.


 **Note:** Real-time point cloud display consumes mobile phone memory. If memory usage is high, the software will clear the display buffer without deleting original device data.



④ **GCP collection:** During data collection, click Add Control Point on the right side of the interface to collect control points. First, click Add Control Point and enter the name of the control point. Then, align the tip of the device handle with the control point to be collected.

Once stable, click Confirm to complete the control point acquisition.



Click on the Control Points List to view all control points collected in the current project, and delete selected control points if needed.



Refer to the following precautions when collecting control points:

- a. When collecting the control point, squat down and get up smoothly.
- b. Avoid people covering the front of the device when the control point is collected.
- c. For the same project, at least four control points are required to complete the coordinate conversion. It is recommended that the control points be evenly distributed in the survey area and avoid being distributed on a straight line.
- d. When collecting control points, there is no requirement for the angle of the equipment itself, and the acquisition of control points can be completed upright, horizontal and backward.
- e. After the control point is collected, wait 15s before finishing the project.
- f. Avoid collecting control points in narrow areas to prevent the laser head from being obstructed.

⑤ **End collection:** After the data scanning is completed, click the orange button on the left to end the collection, and the device will automatically generate a real-time las point cloud file of the current project, store it in the original project-SLAM DATA folder, and shut down after the project is saved.




3.2.10 One-click Collection

The TVGO NEO supports one-click collection via the button located on the front of the battery handle.

- After the device is powered on, the indicator light stays solid blue, indicating the device is in standby mode. Press and hold the collection button at the top of the handle to start initialization. During initialization, ensure the surrounding area is clear of obstructions and the device remains stable. Once initialization is successful, the indicator light changes from solid blue to a blue-green breathing effect, indicating the device has entered scanning mode.
- To end data collection, press and hold the collection button at the top of the handle again. The indicator light will change from blue-green breathing to slow-flashing green, indicating the device is saving data. When the light changes from slow-flashing green back to solid blue, the device has finished saving and has returned to standby mode.

 **Note:** One-click collection cannot log in to the CORS account.



4 Collection Guide

4.1 Route Planning

Before data collection, plan the survey route in advance to ensure optimal scanning results. The fundamental principle of route planning is 'global first, then local.' Proper route planning maximizes the effectiveness of the device's correction algorithms and enhances overall data accuracy.

- Global coverage: Traverse the entire survey area using the shortest possible route to establish a stable positioning map.
- Local refinement: Perform detailed scanning using small loop closures. Progress incrementally to ensure complete coverage of the survey area.

4.2 Loop Requirement

When GNSS signals are unavailable, loop closure is required to maintain positioning accuracy. Loop closure is an important method for improving data precision. The collection route should form closed loops whenever possible.

- Ensure loop overlap is greater than 10%.
- In complex environments, close loops end-to-end and return along the same path if necessary.

4.3 Precautions for Data Acquisition

- TVGO NEO is a precision instrument. It is forbidden to bump or use the surface of the lidar by hand during use. Before data collection, ensure that the surface of the laser head and camera is clean and free of dirt.
- In the process of data collection, avoid fast and large-scale turning and shaking, so as not to affect the accuracy of mapping and the effect of point cloud.
- In the process of data acquisition, try to distance more than 0.5 m from the measured object to achieve good scanning effect.
- When collecting data, it is recommended to control the collection speed at 3-5km/h, and slow down the walking speed appropriately for scenes that require careful scanning or have few features.
- Try to avoid moving pedestrians or vehicles during data collection. If conditions permit, when encountering numerous moving objects, you may stand still sideways and resume scanning after the moving objects have passed.


- During scanning, avoid prolonged blocking of the device by pedestrians. When multiple personnel are working together, the operator should walk at the front.
- During data collection, point the device toward the survey area and monitor the real-time point cloud display throughout the process to avoid missing data.
- When scanning indoor rooms, it is recommended to open all room doors in advance and enter/exit sideways to ensure a good connection between indoor and outdoor data. If you cannot open the door in advance, turn around when you are close to the door, turn the instrument away from the door, open the door with your back and enter.

5 Data Processing

5.1 Data


5.1.1 Data Copying

- Power off the device before copying data.
- Use the original data cable to connect the device to a computer. Open the ALPHA_ALL folder then copy or move the required project data to the computer.
- Do not process data directly from the device storage.



5.1.2 File Structure

The original TVGO NEO project contains five folders: **GPS**, **IMG**, **INFO**, **SCAN**, and **SLAM DATA**. The contents of each folder are as follows:



5.1.3 Data Cleaning

TVGO NEO data cleaning, you can directly delete the engineering data in the TVGO NEO ALPHA _ ALL folder, or format the TVGO NEO data disk.

5.2 Software Installation

The data processing software for the TVGO NEO is CoPre. CoPre is a proprietary 3D data intelligent processing software. It primarily supports data processing for laser scanning systems and aerial survey image data. Data collected by orthophoto cameras and tilt cameras can be processed into point clouds, panoramic images, orthophoto images, 3D models, and other outputs. As the core bridge between data acquisition and processing within TrueView's 3D intelligent product ecosystem, CoPre offers comprehensive functionality with an intuitive, user-friendly interface.

Visit <https://support.TrueView.com/portal/en/kb/m3d/software/copre/1-software-package> to download and install the CoPre software.

5.2.1 Install


Copro2 System and Hardware Requirements Table	
Operating System	Microsoft Windows 7 (64-bit) Microsoft Windows 10 (64-bit)
CPU	Minimum: 2+ GHz processor Recommended: 3.5+ GHz processor
Memory	Minimum: 16 GB Recommended: 64 GB
Graphics Card	Only supports NVIDIA GTX 1050 Ti or higher graphics cards released after 2021
Monitor Resolution	1920×1080 or higher
.NET Environment	.NET Framework Version 4.0

Function	Computing Configuration
One-Click Refinement	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM
HPC True Color Shading	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM
Mesh Modeling	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM
3DGS Modeling	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM
Multi-Station Stitching	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM
In-Vehicle Privacy Blurring	Minimum Configuration: NVIDIA RTX 3050Ti or higher graphics card, Intel Core i7 or higher CPU, 32GB RAM Recommended Configuration: 64GB or More RAM
Calibration	Minimum Configuration: 32GB RAM Recommended Configuration: 64GB or More RAM

5.2.2 Software Registration

CoPre currently supports three types of licensing.


- ① **Registration:** Provide the hardware ID to obtain the registration code for the after-sales personnel of Shanghai TrueView. After entering the registration code, you can obtain the right to use the corresponding function and duration.
- ② **Exchange:** When the computer is connected to the Internet, enter the software exchange code, and the usage rights corresponding to the function and duration.
- ③ **Trial:** When the computer is connected to the Internet, enter the email address or mobile phone number, enter the sent verification code, and the full-featured software module can be used for one month. Each computer can be tried twice at most.



5.3 Data Resolution

5.3.1 New Construction

After the software is installed and authorized, open the CoPre software, click "Project Management-> New", pop up the Create Task dialog box, enter the task name, click the "..." button on the right side of the project data and task path, and select the project data and task path, and then click New.



Create Task

Name: CHC_20260122172344

Project Data: G:\kll\@@2026-01-13-C ...

Directory: G:\kll ...

Units: Meter

Description: Please add workspace related information

Create Cancel


- Task Name: The name of the newly created work task.
- Project data: Original project data copied from the device. Multiple projects can be selected and processed simultaneously.
- Directory: The path for storing intermediate data and achievement data.
- Unit: Meter by default.
- Description: You can manually enter information about the solution task.

Note: Task names, project data paths, and task paths do not support non-English paths and spaces.



5.3.2 Coordinate System Setup

After the new task is completed, enter the coordinate system selection interface.

- When absolute coordinates are not required and only relative measurements are needed—such as for volume calculations, house area measurements, etc.—select the relative coordinate system. In this mode, post-processing can only output point cloud results in the relative coordinate system.




- When absolute three-dimensional spatial coordinates are required—such as for terrain surveying, building facade measurement, or coordinate conversion—select the projected coordinate system. This system supports customization or the use of EPSG standard coordinate systems.



5.3.3 Real-time Point Cloud Loading


After creating a new project, in the SLAM processing module of CoPre, click to load the real-time data to display the real-time point cloud results. The real-time point cloud is stored in the original project/SLAM DATA folder in LAS format.




5.3.4 One-click Refinement

When the real-time point cloud effect cannot meet our needs, we can use one-click refinement to optimize the point cloud.

After the coordinate system is set, click the 'Optimize Data' option.




① **Select projects:** Select the project data that needs to be processed. CoPre supports selecting multiple projects for processing at the same time.




② **SLAM Trajectory optimization:** optimize SLAM results through GNSS data.

Process Mode :

Default: No configuration is required; the system automatically selects the appropriate coordinate system, such as a relative coordinate system or projected coordinate system.




RTK : When GNSS signals are available within the survey area and the system has achieved a fixed RTK solution, the RTK-optimized trajectory function can be enabled to further improve trajectory and point cloud accuracy. This function refines the positioning solution and transforms the point cloud from a relative coordinate framework into an absolute coordinate reference system.



PPK: When satellite signals are available in the survey area and a physical static base station

is deployed during data collection—the PPK optimized trajectory function can be enabled. This function applies a post-processing differential algorithm to generate high-precision POS data, thereby improving overall data accuracy and converting the point cloud from a relative coordinate system to an absolute coordinate system.



- PPK calculation supports the use of TrueView cloud base stations or self-built base stations.
- When using a self-erected base station, set it up over a known point and ensure its static observation covers the device's data collection period. After operation, copy the base station static file (Renix 3.02 or HCN format) to the original project/GPS/Base folder. The software will automatically detect it. Alternatively, click Add on the physical base station interface to manually select the file and enter the base point coordinates.

Optimize Data

1 Select Project 2 Slam Trajectory Optimization 3 Result Settings

Please select the projects that need to be processed in the list

Project List

xiananfang6

Solve Mode ☐ Default ☐ Slam ☐ RTK ☒ PPK

Note: Using PPK can optimize trajectory accuracy to further improve point cloud accuracy. It is better than RTK optimization.
PPK scenarios: Outdoors, especially scenes with poor RTK correction or even no RTK; Unavailable scenes: Indoors.

Base Station Settings

☐ Cloud Base Station ☒ Field Base Station

Base1

Base Station Coordinate

Name: 20260306-085521_1.26o

CS Type: ☐ WGS84 BLH

B: 30:36:00.004760 N

L: 114:17:59.982247 E

H (m): 31.5699

Antenna Settings

Measured Height (m): 0.0000

Measure To: Unknown

Antenna Phase Height (m): 0.0000

Manufacturer: Unknown

Antenna Type: Unknown

Sampling Rate (s): 1.0000

SLAM: When satellite signals are unavailable in the survey area, or absolute coordinates are not required and only relative measurements are needed, select Pure SLAM Solution. Without GNSS optimization, the system will output point clouds in a relative coordinate system.

Optimize Data

1 Select Project 2 Slam Trajectory Optimization 3 Result Settings

Please select the projects that need to be processed in the list

Project List

xiananfang6

Solve Mode ☐ Default ☒ Slam ☐ RTK ☐ PPK

Note: Using PPK can optimize trajectory accuracy to further improve point cloud accuracy. It is better than RTK optimization.
PPK scenarios: Outdoors, especially scenes with poor RTK correction or even no RTK; Unavailable scenes: Indoors.

☐ Using TGCP to optimize trajectory

Note: Using control points can optimize trajectory to further improve point cloud accuracy. This step can be skipped if there are no control points.

Using TGCP to optimize trajectory: Using matched trajectory control points to correct SLAM


accuracy and transform coordinates.

- Trajectory control points are used to correct SLAM accuracy and transform the point cloud from a relative coordinate system to the trajectory control point coordinate system. This method is suitable for scenarios where trajectory control points have been collected in the field. Trajectory control point matching must be completed prior to use. If no trajectory control points are available, this optimization can be skipped.
- Field-collected trajectory control points will appear in the Real-time Acquisition Points list. Click 'Import' above 'Externally imported TGCP' on the right to import known control point coordinates. Supported formats include .csv and .txt. Ensure the imported point names match the real-time collected ones—control points will be matched automatically by name. After matching, the error can be calculated, and points with large errors can be deselected from the calculation.

The screenshot shows the 'Optimize Data' application window with three tabs: '1 Select Project', '2 Slam Trajectory Optimization' (active), and '3 Result Settings'. A yellow banner at the top of the active tab says 'Please select the projects that need to be processed in the list'. On the left, under 'Project List', the project 'xiananfeng6' is selected. The main area of the 'Slam Trajectory Optimization' tab contains the following elements:

- Solve Mode:** Radio buttons for 'Default', 'Slam' (selected), 'RTK', and 'PPK'. A note states: 'Note: Using PPK can optimize trajectory accuracy to further improve point cloud accuracy. It is better than RTK optimization. PPK scenarios: Outdoors, especially scenes with poor RTK correction or even no RTK; Unavailable scenes: Indoors.'
- Using TGCP to optimize trajectory:** A checked checkbox.
- Real-time collection points(point numbers:0):** A table with columns: Name, Type, X, Y. It is currently empty.
- Externally imported TGCP:** A table with columns: Name, E, N, H. It is currently empty.
- Buttons:** 'Import' and 'Clear' are above the 'Externally imported TGCP' table. 'Calculate Error' and 'Display in 3D View' are at the bottom right.
- Legend:** 'Paired' (green square), 'Not Found' (red square), and 'Output Reports' (checkbox with a help icon).
- Status Message:** A red text box at the bottom left of the main area says: 'The current project does not have real-time collected points.'
- Footer:** 'Cancel', 'Advanced', 'Apply to Other Projects', 'Back', and 'Next' buttons.

Slam Solve Advanced setting



Process Template:

Auto Detect: The real-time algorithm automatically identifies scene features and selects the appropriate mode.

Indoor space: Force switch to indoor mode.

Outdoor space: Force switch to outdoor mode.

Narrow space: Force switch to narrow space mode.

Custom mode: Modifying any advanced parameter will activate custom status.

Loop Closure Strategy:

Turn Down: Reduces incorrect loop closures and corrects point cloud stratification caused by wrong closures, but may lead to misalignment at loop closure positions.

Turn Up: Corrects unclosed trajectory data, but may capture incorrect loop closures and cause point cloud misalignment.

GNSS Data Weight:

Turn Down: Suitable for data with GNSS signal but point cloud stratification issues; helps reduce stratification.

Turn Up: Suitable for datasets acquired under stable GNSS conditions. Performance may degrade in areas with weak or unstable satellite signals.

Point Cloud Matching Strategy:

Turn Down: Reduces the LiDAR weighting factor, applies a conservative matching strategy, and suppresses fine surfaces and noise. This setting is recommended for correcting local point cloud misalignments caused by matching errors.

Turn Up: Increases the LiDAR weighting factor, applies a more aggressive matching strategy, and attempts to align fragmented surfaces as completely as possible. This setting is recommended for weak-feature environments where point cloud drift is likely to occur.

IMU Data Weight:

Turn Down: Reduces the weighting factor of IMU data to limit its influence on the overall solution. This setting is recommended for datasets with strong point cloud features and is effective in mitigating trajectory drift.

Turn Up: Increases the weighting factor of IMU data to strengthen its influence on the overall solution. This setting is recommended for datasets with weak point cloud features and can improve robustness in cases where the solution may otherwise fail.

Vertical Optimization Weight:

Turn Down: Reduces the optimization strength in the vertical direction. This setting is recommended for scenes with significant elevation variations.


Turn Up: Increases the optimization strength in the vertical direction, enhancing the flatness of ground and ceiling point clouds.

Laser Available Range:

Minimum Range: Defines a spherical exclusion zone centered on the device. Point clouds within this radius will be filtered out. Increase this value when excessive short-range noise is present.

Maximum Range: Defines the maximum effective range centered on the device. Point clouds beyond this radius will be filtered out. Increase this value when long-range point cloud registration errors occur.

③ **Result setting:** Calculate and set the engineering data, and output the corresponding results.




Point cloud: Output Point Cloud Data.

Panoramic Images: Output panoramic images.

Mesh Model: Build mesh models: The mesh model is generated by fusing SLAM point cloud data with images. Currently, the model can be exported in two formats: **OSGB** and **OBJ**.

3DGS Model: Build 3D Gaussian models: Compared with traditional mesh modeling, the 3D Gaussian (3DGS) model provides more realistic visual effects. Currently, the model can be exported in one format: **PLY**.

Advanced



Point Cloud Optimization:

Reduces the density of the point cloud to enhance the precision of local structural details in the display.

Point Cloud Denoise:

Removes floating noise from the point cloud to improve the overall visual quality.

Note: This option may also remove some point cloud data in sparsely populated or unevenly distributed areas

AI Human Filter:

Enabled: Filters out nearly all human points from the point cloud. Note that this may create partial holes in the point cloud.

Disabled: Disables the filter. Use this setting if undesired point cloud holes appear (e.g., caused by posters or photos).

Remove Unshaded Points:

Points with an RGB value of (0, 0, 0) will be excluded from processing. This helps prevent certain white or dark points from negatively affecting the overall appearance of the point cloud.

Multiple Return

Checked: Output the multiple echo point cloud data.

Unchecked: Output the single echo point cloud data.

3D Distance Filter:


Filter the point cloud by the distance to the center of the laser.

Intensity Filter:

Filter the point cloud by the intensity.

5.3.5 Results Browsing

- In Outcome Project, select the desired project.
- Right-click 'Display Trajectory' to load the POS Trajectory into the left view.
- Select a portion of the trajectory by either clicking two points on the result trajectory or holding down the left mouse button to draw a selection box.
- The point cloud corresponding to the selected trajectory will be loaded into the Point Cloud view.
- In the 3D view, choose Render to visualize the point cloud.



5.4 Point Cloud Display



Switch point cloud to elevation rendering



Switch point cloud to intensity rendering



Switch point cloud to color rendering




Switch the point cloud to precision rendering, the smaller the value, the more accurate the relative precision of the point cloud



Toggle ribbon strips for point clouds

5.5 Export Results

- After checking the data of the point cloud, if it meets the requirements, the results of the point cloud can be exported.
- In SLAM processing, click the 'Export' button, select the project that needs to be exported, set the coordinate type, file format, coloring range, segmentation, export range and export directory, and click 'Confirm' to export the achievement point cloud.



6 Frequently Asked Problems and Solutions

6.1 TVGO NEO Host

- The device cannot be turned on: check the battery power of the device and whether the handle battery is installed in place.
- The mobile phone cannot find the WIFI signal of the device: check whether the device is turned on.

6.2 TrueView Go

- TrueView Go is disconnected from the device during the collection process: check whether there are other APPs or other devices connected to TVGO NEO WIFI.
- The CORS account cannot be successfully logged in the TrueView Go collection settings. Check if the tablet has a mobile network.

7 Daily Use and Precautions

7.1 Use

- ⊗ 1. For the sake of equipment safety and the possibility of more noise in point clouds, it is forbidden to use it in rainy, snowy and foggy weather, and it is forbidden to work under strong wind and dust.
- ⊗ 2. It is forbidden to expose equipment and its accessories to extreme temperatures. The operating temperature and storage temperature shall not be lower or higher than the temperature specified in the specification.
- ⊗ 3. When the product is transferred from cold to warm, water vapor may condense on some elements inside the scanner. To avoid this, it is recommended to place the scanner in a sealed plastic bag before transferring it. After the temperature of the equipment is basically the same as that of the outside world, and the condensed water evaporates, turn on the equipment again.

7.2 Daily Service Specification

The TVGO NEO measurement system is a complex and precise surveying and mapping system. In daily carrying, handling, use and storage, only through correct use and proper maintenance can the accuracy of the instrument be better guaranteed and its service life be extended. When using this TVGO NEO measurement system, you should pay attention to the following:

1. The user cannot disassemble the instrument by himself. If there is a failure, please contact the supplier.
2. This instruction book is a comprehensive instruction book for TVGO NEO measurement system. Please choose the corresponding operation method according to the specific operation. If you have any questions, please contact the technical staff of Shanghai TrueView.
3. Connect the equipment strictly according to the connection method in the installation manual, check whether the screws and plug-ins of the structural parts are loose, and regularly clean the surface of the equipment, the laser window mirror and the camera lens with a cleaning kit. Follow the following steps during the cleaning process:
 - a. Choose a place with less dust, and use a lens cloth to remove dust from the surface of the lidar and camera.
 - b. Use wet wipes to gently laser window mirrors and camera lenses, as well as residual dust and fingerprints in gaps.
 - c. Clean the main body of the LiDAR and camera with a wet wipe, using a soft towel if necessary. **Note:** Do not use alcohol or other corrosive liquids on non-metallic parts of the main body or camera.
4. Prevent the instrument from being strongly impacted or vibrated.

5. After the instrument is used, it should be packed in time. Before packing, it is necessary to ensure that the instrument and the instrument box are dry.
6. If the instrument needs to be operated continuously for extended periods or under special conditions such as high humidity, please consult the Shanghai TrueView Technology Center for relevant precautions. Failures occurring under such special conditions are not covered by the product warranty.
7. Handle the equipment with care during use to avoid contamination or surface scratches. Surveyors or any personnel must not sit on the equipment or its packaging under any circumstances.

7.3 Equipment Transportation

1. The equipment is provided with a dedicated instrument box. During transportation or relocation, place the equipment inside the instrument box and secure it in position using seat belts or other restraining measures. Avoid collisions between the instrument box and the vehicle body to minimize impact and vibration.
2. During transportation, ensure that consignors or handlers avoid improper operations. Inform all personnel that the equipment is a precision instrument requiring careful handling. Clearly label the equipment as 'Fragile'.
3. For express shipping, in addition to the instrument box, an outer carton should be used. Fill the space between the instrument box and the outer carton with shock-absorbing materials such as cotton or foam.

7.4 Equipment Storage

1. When not in use, place the equipment neatly inside its instrument box. The instrument box should be placed on a table or shelf in an organized manner and **must not be stacked**.
2. The storage room should be clean, dry, and well-ventilated. Replace the desiccant in the instrument box regularly to maintain optimal humidity conditions.

FCC Warning

15.19 Labeling requirements.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

15.21 Information to user.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.105 Information to the user.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Absorption Rate (SAR) information:

This device meets the government's requirements for exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

FCC RF Exposure Information and Statement

The SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. This device was tested for typical body-worn operations with the back of the device kept 0mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain an appropriate separation distance between the user's body and the back of the device. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with FCC RF exposure requirements, and should be avoided. Use only the supplied or an approved antenna.

ISED Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference.
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

L' émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d' Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L' exploitation est autorisée aux deux conditions suivantes:

- (1) L' appareil ne doit pas produire de brouillage;
- (2) L' appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d' en compromettre le fonctionnement.

This EUT is compliance with SAR for general population/uncontrolled exposure limits in ISSED RSS-102 and had been tested in accordance with the measurement methods and procedures specified in IEC/IEEE 62209-1528. This equipment should be installed and operated with minimum distance 0 mm between the radiator and your body/limbs. This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

Cet EUT est conforme aux limites d'exposition SAR pour la population générale/non contrôlée de l'ISDE RSS-102 et a été testé conformément aux méthodes et procédures de mesure spécifiées dans la norme IEC/IEEE 62209-1528. Cet équipement doit être installé et utilisé à une distance minimale de 0 mm entre le radiateur et votre corps/membres. Cet appareil et ses antennes ne doivent pas être situés ou fonctionner en conjonction avec une autre antenne ou un autre émetteur.

Operation of this device is restricted to indoor use only. (5150-5250MHz)

Le fonctionnement de cet appareil est limité à une utilisation en intérieur uniquement. (5150-5250MHz)