


App Settings and Updates



To fully utilize the XIFOWE L1 smart taillight, please scan the QR code ****above**** to download the latest version of the ****XIFOWE APP****—rest assured, it's secure and free. Within the app, you can customize your device with graphic designs, adjust lighting modes, and access future services such as firmware upgrades.



We welcome and value any suggestions or feedback you may have while using our product. We will closely review your input to continuously improve our services and product offerings.




Product Body*1



Mounting Rod Pad*1



Mounting Bracket*1



USB-C Charging Cable*1



Rubber Bands*2

Comes as a free gift with the product

1. Secure the mounting bracket and base rod pad together as one unit.

*This component is suitable for round and square bicycle seat posts.



2. Secure the seat post pad and mounting bracket to the seat post using a suitable rubber band.

3. Align the latch on the back of the product body with the slot on the mounting bracket, then rotate it into the secure position.

(At this point, the product's USB charging port should be facing downward, which is the standard orientation for use.)



We offer 24/7 customer support. If you encounter any issues during installation, please contact us for assistance.

1. Press and hold the power button to turn the device on/off.
2. Press the power button once to cycle through light modes.
3. Press the power button twice to display remaining battery level.
4. Features memory function: the tail light mode remains consistent with the last setting when turned off.
5. The built-in motion sensor automatically triggers the taillights to flash when the vehicle transitions from motion to stationary, providing a visual warning (this feature must be manually enabled via the companion mobile app).
6. When the battery level drops to 20%, the display screen will blink the battery icon and the taillights will automatically power off to protect the battery and extend its service life.
7. When the bicycle taillight is charging, it displays the current battery level in real time. Press the power button on the side of the taillight once to disable the accidental touch prevention function, then press it again to turn off the battery indicator; press it once more to turn the indicator back on.

Note: Ensure the battery is sufficiently charged before riding. If the product is stored for an extended period, maintain the battery charge between 40% and 60%. Regular charging extends battery life. Recommended charging input: 5V/2A.



XIFOWE[®]

Bicycle Tail Light Series

Product Specifications

- Model: L1
- Battery Type: Built-in Rechargeable Lithium Battery / 1000mAh
- Operating Temperature Range: -10°C to 50°C (14°F to 122°F)
- Charging Temperature Range: 0°C to 45°C (32°F to 113°F)
- Recommended Input Specification: DC 5V 2A
- Waterproof Rating: IPX5

Safety and Product Information Notes

Warning

Failure to observe the following potential hazards may result in serious injury or even death.

Battery Warnings

This product uses a rechargeable lithium battery. Failure to comply with the following guidelines may shorten the battery life, damage the device, or pose risks of fire, chemical burns, electrolyte leakage, and injury.

- Do not disassemble, modify, pierce, squeeze, or damage the battery to avoid hazards.
- Do not expose the device or battery to flames, explosions, or other dangerous environments.
- Do not place the device in high-temperature environments, such as dryers or cars under direct sunlight.
- Do not immerse the battery in water or other liquids.
- Do not perform frequent overcharging. Do not charge the battery near fire or under extremely high-temperature conditions. Strictly follow the charging requirements to avoid hazards caused by excessive current.
- If the product is left unused for an extended period, store it with the battery charge maintained between 40% and 60% to prolong its service life.

Warranty Terms

Thank you for purchasing the XIFOWE bicycle tail light series. Please read the following terms carefully.

1. This product has passed strict quality inspections. For failures caused by product quality issues under normal use conditions, we provide free warranty service within the warranty period.
2. Within 7 days (inclusive) from the date of purchase, if there is a quality problem with the product itself, unconditional return or exchange is allowed.
3. The warranty period for the main unit of the product is 12 months from the date of purchase, and the warranty period for other accessories is 3 months. For warranty repairs, the product must be packed in the original packaging and shipped via designated logistics. Otherwise, the user shall bear the shipping costs or losses caused during transportation.

*The following situations are not covered by the warranty:

- Beyond the valid warranty period.
- Any damage caused by improper use, maintenance, or storage.
- Product damage caused by failure to use or install in accordance with the manual.
- Unauthorized repair, misuse, collision, negligence, abuse, liquid ingress, accident, modification, or use of non-original accessories without clear authorization.
- No valid invoice or purchase record.
- The invoice or purchase record does not match the actual product.
- Other failures and damages not caused by the product's own design, manufacturing, quality, or other related issues.
- Wear and tear, dirt (such as scratches) caused by normal use, as well as damage caused by human factors such as contact with chemical agents, sharp objects, dropping, or squeezing.
- Damage caused by force majeure.

After-Sales Service Period

- Our company provides lifelong after-sales service for the product.
- After the product exceeds the warranty period, only the cost price will be charged for repairing product failures, and only the labor and accessory cost prices will be charged for repairing human-caused damages.
- ***Our company reserves the right to modify and interpret the above contents.**

FCC Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complies with the FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and any part of your body.

Certified Model: L1
Hangzhou Aidan E-Commerce Co., Ltd.
Room 1726, Building 2, Huashengda Times Center
Xiaohang District, Hangzhou 310000
Email: Support@XIFOWE.com
Version: V1.0