

USER GUIDE

Pairing Instructions for Chevrolet GMC Replacement Remotes M3N32337100

Before operating this equipment, please read these instructions carefully, paying particular attention to safety warnings and cautions. Failure to use this product correctly may result in damage and make the remote control unsuitable for the vehicle.

1. All currently **programmed** and **new remotes** must be reprogrammed to your vehicle. Please have all remotes in hand at time of programming.

2. You must have at least one of original keys or fobs for programming process.

3. Only the original functions of the remote control can be used on the new key, regardless of the buttons on the new key. This key doesn't add remote features that your vehicle did not have before.


4. The vehicle allows add up to 4 total remotes.

5. Do not use the programmer while the vehicle is in motion. Unplug it from the OBD port before driving the vehicle. An alarm will sound reminding you to remove it after 5 minutes.

PROGRAMMING INSTRUCTIONS


Instructions have timing requirements. If you wait too long between steps, your vehicle's computer may time out, requiring you to start over. Once plugging the programmer in, you will have 2 MINUTES to program all new and existing remotes to the vehicle.

① Enter the vehicle and close all doors.

②  Insert the Key into ignition and turn to ON position. DO NOT start the engine.

③ Insert the programmer into your vehicle's on-board diagnostic(OBD) port. The programmer

will beep 3 times rapidly. You will see the message "Remote Key Learning Active" in the driver information center.

④  PRESS and HOLD the LOCK and UNLOCK button simultaneously for 15 seconds on the remote or until you hear a beep from the vehicle.

Note: your vehicle may or may not provide feedback such as the door lock cycling, a message on the dashboard, or a chime.

⑤ Perform step 4 for all additional remotes.

⑥ When all remotes have been added, turn off the ignition and unplug the programmer.

⑦ Test each remote. If remotes were not programming successful, repeat the process from step 1.

Note: Some vehicles may need to have the engine started and stopped, and the driver's door opened and closed before the remotes will work.

FREQUENTLY ASKED QUESTIONS

Q: Can I use the same PROGRAMMER on other vehicles?

A: No, the programmer will be locked to the first vehicle that uses it. You may add more keys to the same vehicle again as needed, but it will not work on different vehicles.

Q: Where is the location of OBD port

A: This port located under steering column, near the brake pedals.