

User Guide Amana AFI2538AEB4 Refrigerator

Table of contents

- REFRIGERATOR SAFETY
- INSTALLATION INSTRUCTIONS
- REFRIGERATOR USE
- REFRIGERATOR CARE
- TROUBLESHOOTING
- WATER FILTER CERTIFICATIONS
- PRODUCT DATA SHEETS
- WARRANTY

IMPORTANT SAFETY INSTRUCTIONS WARNING:

To reduce the risk of fire, electric shock, or injury when using your refrigerator, follow these basic precautions:

- Plug into a grounded 3 prong outlet.
- Do not remove ground prong.
- Do not use an adapter.
- Do not use an extension cord.
- Disconnect power before servicing.
- Replace all parts and panels before operating.
- Remove doors from your old refrigerator.
- Use nonflammable cleaner.
- Keep flammable materials and vapors, such as gasoline, away from refrigerator.
- Use two or more people to move and install refrigerator.
- Disconnect power before installing ice maker (on ice maker kit ready models only).
- Use a sturdy glass when dispensing ice (on some models).

SAVE THESE INSTRUCTIONS

- Proper Disposal of Your Old Refrigerator
- Suffocation Hazard
- Remove doors from your old refrigerator.
- Failure to do so can result in death or brain damage.

IMPORTANT:

1. Child entrapment and suffocation are not problems of the past. Junked or abandoned refrigerators are still dangerous even if they will sit for "just a few days." If you are getting rid of your old refrigerator. please follow these instructions to help prevent accidents.
2. Before You Throw Away Your Old Refrigerator or Freezer: Takeoff the doors.
3. Leave the shelves in place so that children may not easily climb inside.

INSTALLATION INSTRUCTIONS

- Excessive Weight Hazard
- Use two or more people to move and install refrigerator.
- Failure to do so can result in back or other injury.
- When Moving "our Refrigerator:
- Your refrigerator is heavy. When moving the refrigerator for cleaning or service. be sure to protect the floor.
- Always pull the refrigerator straight out when moving it.
- Do not wiggle or "walk" the refrigerator when trying to move it. as floor damage could occur.
- Remove the Packaging
- Remove tape and glue residue from surfaces before turning on the refrigerator.
- Rub a small amount of liquid dish soap over the adhesive with your fingers.
- Wipe with warm water and dry.
- Do not use sharp instruments. rubbing alcohol. flammable fluids. or abrasive cleaners to remove tape or glue. These products can damage the surface of your refrigerator.
- For more information. see "Refrigerator Safety."
- Dispose of/recycle all packaging materials.

Clean Before Using

1. After you remove all of the packaging materials. clean the inside of your refrigerator before using it. See the cleaning instructions in "Refrigerator Care."
2. Do not clean glass shelves or covers with warm water when they are cold. Shelves and covers may break if exposed to sudden temperature changes or impact. such as bumping.
3. For your protection. tempered glass is designed to shatter into many small. pebble-size pieces. This is normal. Glass shelves and covers are heavy. Use special care when removing them to avoid impact from dropping.

Explosion Hazard

- Keep flammable materials and vapors, such as gasoline, away from refrigerator.
- Failure to do so can result in death, explosion, or fire.
- To ensure proper ventilation for your refrigerator, allow for a 1/2" (1.25 cm) space at the top and behind the refrigerator.
- If your refrigerator has an ice maker, allow extra space at the back for the water line connections.
- When installing your refrigerator next to a fixed wall, leave a 33/4" (9.5 cm) minimum space between the refrigerator and wall to allow the door to swing open.

NOTE:

- It is recommended that you do not install the refrigerator near an oven, radiator, or other heat source.
- Do not install the refrigerator in a location where the temperature will fall below 55°F (13°C).

Electrical Shock Hazard

- Plug into a grounded 3 prong outlet.
- Do not remove ground prong.
- Do not use an adapter.
- Do not use an extension cord.
- Failure to follow these instructions can result in death, fire, or electrical shock.
- Before you move your refrigerator into its final location, it is important to make sure you have the proper electrical connection.
- Recommended Grounding Method A 115 Volt, 60 Hz, AC only, 15- or 20-amp fused, grounded electrical supply is required.
- It is recommended that a separate circuit serving only your refrigerator be provided.
- Use an outlet that cannot be turned off by a switch.
- Do not use an extension cord.

NOTE:

- Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source.
- When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting.
- See "Using the Controls."

- Gather the required tools and parts before starting installation.
- Read and follow the instructions provided with any tools listed here.

TOOLS NEEDED:

- Flat-blade screwdriver 1/4"Nut driver
- 7/16" and 1/2"Open-end or two 1/4"Drill bit adjustable wrenches Cordless drill

IMPORTANT:

- All installations must meet local plumbing code requirements.
- Do not use a piercing-type or 3/16" (4.76 mm) saddle valve which reduces water flow and clogs more easily.
- Use copper tubing and check for leaks. Install copper tubing only in areas where the household temperatures will remain above freezing.

Water Pressure

- A cold water supply with water pressure of between 35 and 120 psi (241 and 827 kPa) is required to operate the water dispenser and ice maker. If you have questions about your water pressure. call a licensed. qualified plumber.
- Reverse Osmosis Water Supply **IMPORTANT:** The pressure of the water supply coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 35 and 120 psi (241 and 827 kPa).
- If a reverse osmosis water filtration system is connected to your cold water supply. the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).
- If the water pressure to the reverse osmosis system is less than 40 to 60 psi (276 to 414 kPa): Check to see whether the sediment filter in the reverse osmosis system is blocked.

Replace the filter if necessary.

- Allow the storage tank on the reverse osmosis system to refill after heavy usage.
- If your refrigerator has a water filter. it may further reduce the water pressure when used in conjunction with a reverse osmosis system.
- Remove the water filter. See "Water Filtration System."
- If you have questions about your water pressure. call a licensed. qualified plumber.
- Read all directions before you begin.

IMPORTANT:

1. If you turn the refrigerator on before the water line is connected. turn the ice maker OFF
2. Connect to Water Line

3. Unplug refrigerator or disconnect power.
4. Turn OFF main water supply. Turn ON nearest faucet long enough to clear line of water.
5. Locate a 1/2" to 1 1/4" (12.7 mm to 31.8 mm) vertical cold water pipe near the refrigerator.
6. Make sure it is a cold water pipe.
7. Horizontal pipe will work, but drill on the top side of the pipe, not the bottom. This will help keep water away from the drill and normal sediment from collecting in the valve.
8. Determine the length of copper tubing you need. Measure from the connection on the rear of the refrigerator to the water pipe. Add 7 ft (2.1 m) to allow for cleaning.
9. Use 1/4" (6.35 mm) O.D. (outside diameter) copper tubing.
10. Be sure both ends of copper tubing are cut square.
11. Using a cordless drill, drill a 1/4" hole in the cold water pipe you have selected.

A. Cold water pipe B. Pipe clamp C. Copper tubing D. Compression nut

E. Compression sleeve F. Shutoff valve

G. Packing nut

Connect to Refrigerator

- Remove plastic cap from water supply connection.
- Place brass nut and compression sleeve on copper tube end as shown.

A. Brass nut

B. Compression sleeve

- Place end of copper tubing into plastic water valve supply line. Slide the brass nut over the sleeve and screw the nut into supply line.
- Using an adjustable wrench, hold the nut on the plastic water line to keep it from moving. Then, with a second wrench turn the nut on the copper tubing counterclockwise to completely tighten.
- Do not overtighten.
- Check connection by pulling on the copper tubing.

5. Attach the copper tubing to the refrigerator with a "P" clamp.

NOTE:

- Allow 24 hours to produce the first batch of ice. Discard the first three batches of ice produced.
- Allow 3 days to completely fill the ice container.
- All graphics referenced in the following instructions are included later in this section after "Final Steps."

- Remove and Replace Handles

Style 1 - Metal Handles

1. Using a 3/32" Allen wrench. loosen the two set screws located on the side of each handle. See Metal Handle graphics and 2.
2. Pull the handle straight out from the door. Make sure you keep the screws for reattaching the handles.
3. To replace the handles. reverse the directions.
4. Style 2 - Plastic Handles To Remove Handles:
5. Grasp the lower part of the handle firmly. slide the handle up and pull the handle straight out from the door. See Plastic Handle graphics 1 and 2.

To Replace Handles:

- Position the handle so that the large holes in the mounting clips are down and align the holes with the door studs.
- Rotate the handle so that the mounting clips are flat against the door and slide the handle down to engage. See Plastic Handle graphics 1 and 2.
- Remove Doors and Hinges

IMPORTANT:

- Remove food and any adjustable door or utility bins from doors.
- Keep the refrigerator doors closed until you are ready to lift them free from the cabinet.

NOTE:

- Provide additional support for the refrigerator door while the hinges are being removed.
- Do not depend on the door gasket magnets to hold the door in place while you are working.

TOOLS NEEDED:

1. 5Ae". /8". /4" hex-head socket wrench. #2 Phillips screwdriver. and a flat-blade screwdriver.
2. Unplug refrigerator or disconnect power.
3. Remove the base grille. Grasp the grille firmly and pull it toward you.
4. Starting with the right-hand side door. remove the parts for the top hinge as shown in Top Hinge graphic.
5. Lift the refrigerator door from the bottom hinge pin.
6. Remove the shim from the bottom hinge pin and keep it for later use. See Bottom Hinge graphic.
7. Remove top hinge cover from left side refrigerator door.

8. Disconnect the wiring plug located on top of the hinge by wedging a flat-blade screwdriver or your fingernail between the two sections.
9. See Connections graphic.
10. Disconnect the water line by holding the tabbed section of the water line while turning the black locking collar clockwise.

See Connections graphic.

- Two people may be required to remove and replace the freezer drawer. Graphics are included later in this section.
- Remove Drawer Front
- Open the freezer drawer to full extension.
- Loosen the four screws attaching the drawer glides to the drawer front. See Drawer Front Removal graphic.

NOTE:

- Loosen screws three to four turns. Keep the screws in the drawer front.
- Lift drawer front upward and off the screws. See Drawer Front Removal graphic.
- Replace Drawer Front
- Slide the drawer glides out of the freezer compartment.
- Insert the screws in the top of the drawer front into the slots in the drawer brackets.
- See Drawer Front Replacement graphic.
- Pull the drawer brackets toward you to position the two screws in the bottom of the drawer front into the brackets.
- See Drawer Front Replacement graphic.
- Completely tighten the four screws.

Style 1 - Front and rear leveling

- Using a 3/8" hex driver, turn the roller adjustment screw(s) on each side to raise or lower that side of the refrigerator.

NOTE:

- Having someone push against the top of the refrigerator takes some weight off the adjustment screws and rollers. This makes it easier to turn the screws.
- It may take several turns of the roller adjustment screw to adjust the tilt of the refrigerator.
- To raise, turn the roller adjustment screw to the right.
- To lower, turn the roller adjustment screw to the left.

- Turn the brake foot clockwise until it is firmly against the floor to keep the refrigerator from rolling forward when the freezer drawer is pulled open.

Leveling screw

- Using a 1/4"hex driver. turn the leveling screw on each side to raise or lower that side of the refrigerator.

NOTE:

- Having someone push against the top of the refrigerator takes some weight off the leveling screws. This makes it easier to turn the screws.
- It may take several turns of the leveling screw to adjust the tilt of the refrigerator.
- To raise. turn the leveling screw clockwise.
- To lower. turn the leveling screw counterclockwise.

NOTE:

1. Your refrigerator may have a rear roller adjustment screw on each side. To raise or lower the rear of the refrigerator. use a 3/8"hex driver to turn the screws.
2. Open the door again to make sure that it closes as easily as you like. If not. tilt the refrigerator slightly more to the rear by turning both leveling screws clockwise.
3. It may take several more turns. and you should turn both screws the same amount.

REFRIGERATORUSE

- There are two refrigerator compartment doors. The doors can be opened and closed either separately or together.
- There is a vertically-hinged seal on the left refrigerator door.
- When the left side door is opened. the hinged seal automatically folds inward so that it is out of the way.
- When both doors are closed. the hinged seal automatically forms a seal between the two doors.

Freezer Refrigerator

- Adjusting Controls
- The REFRIGERATOR control adjusts the refrigerator compartment temperature.
- The FREEZER control adjusts the freezer compartment temperature.
- If you need to adjust the temperature in either the refrigerator or freezer compartment. use the settings listed in the chart as a guide.

IMPORTANT:

- When the power is on, the temperature display shows the set point temperature of the compartment.
- Wait 24 hours for your refrigerator to cool completely before adding food. If you add food before the refrigerator has cooled completely, your food may spoil.

NOTE:

- Adjusting the refrigerator and freezer temperature controls to a colder than recommended setting will not cool the compartments any faster.
- The recommended settings should be correct for normal household refrigerator use. The controls are set correctly when milk or juice is as cold as you like and when ice cream is firm.
- If the temperature is too warm or too cold in the refrigerator or freezer, first check the air vents to be sure they are not blocked before adjusting the controls.

To Turn Off/On: IMPORTANT:

1. Depending on your model you may have a control center with an On/Off button (Style 1) or you may have a control center without an On/Off button (Style 2).
2. The On/Off control turns off cooling for both compartments and turns off the dispenser. It does not disconnect power to the refrigerator.
3. Style 1 - Press and hold the On/Off button for three seconds.
4. The red LED will light up to indicate that cooling is Off. Press the On/Off button again to turn on the cooling.
5. The LED will turn off.
6. To Adjust Set Point Temperatures: The first touch of the (+) or (-) touch pad displays the current temperature set point.
7. Press the (+) or (-) touch pads until the desired temperature set point is displayed.

NOTE:

- Except when first turning on the refrigerator, do not adjust either temperature control more than one setting at a time. Wait 24 hours for the temperature to stabilize between adjustments.

Max Cool

- The max cool feature assists with periods of high refrigerator use, full grocery loads, or temporarily warm room temperatures.
- Press the Max Cool touch pad to set the freezer and refrigerator to the lowest temperature settings.

- Press the Max Cool touch pad again to return to the normal refrigerator set point.

NOTE:

- The Max Cool feature will automatically shut off in approximately 2 hours. When Max Cool is on, you cannot adjust the temperature.
- Power off cooling system press 3 sec

Humidity Control (on some Models)

- The humidity control feature turns on a heater to help reduce moisture on the door hinge seal. Use in humid environments or when you notice moisture on the door hinge seal. The refrigerator uses more energy when Humidity Control is on.
- Press Humidity Control to turn on the door heater. Press Humidity Control again to turn off the heater. The LED will be illuminated when Humidity Control is on.
- Door Alarm The Door Alarm feature sounds a chime every few seconds when the refrigerator door has been left open for 5 continuous minutes.
- The chime will sound until the door is closed or Door Alarm is turned off.
- Press the Door Alarm touch pad to turn this feature on or off.
- The indicator light will be lit when the Door Alarm feature is on.
- You can control the amount of humidity in the moisture-sealed crisper. Adjust the control to any setting between LOW and HIGH.

User Preferences

- The control center allows you to set user preferences, if desired.
- Temperature Display (FC) This preference allows you to change the temperature display.

F - Temperature in degrees Fahrenheit

C - Temperature in degrees Celsius

- Alarm (AL) This preference allows you to turn off the sound of all alarms.
- ON - You will hear the alarm sound.
- OFF - You will not hear the alarm sound.
- Auto Light Level Selection (LL) This preference allows you to adjust the dispenser light level from dimmest to brightest (settings 1 through 9).

NOTE:

1. The Auto Light feature on the control center must be selected to activate this preference.
2. Sabbath Mode (SAB) ON - All control center lights, interior lights and alarm tones will be disabled.
3. OFF - All control center lights, interior lights and alarm tones will be enabled.



NOTE:

- Press the door alarm touch pad for three seconds to restore all lights.

To Access the User Preferences Menu:

1. Press and hold the Door Alarm touch pad for three seconds.
2. The preference name will appear in the Freezer display and the preference status (F or C) or (ON or OFF) will appear in the Refrigerator display.
3. Use the Freezer (+) or (-) touch pads to scroll through the preference names. When the desired preference name is displayed, press the Refrigerator (+) or (-) touch pads to change the preference status.
4. Set your preferences by pressing and holding the Door Alarm touch pad for three seconds.
5. The ice maker and storage bin are located in the upper left-hand side of the refrigerator compartment.

Turning the Ice Maker On/Off

- The On/Off switch is located on the ice maker.
- To turn on the ice maker, press the switch to the ON position.
- To manually turn off the ice maker, press the switch to the OFF position.
- NOTE: Your ice maker has an automatic shutoff. The ice maker sensors will automatically stop ice production, but the control will remain in the ON position.
- Removing and Replacing Ice Storage Bin

To Remove the Ice Storage Bin:

- Hold the base of the storage bin and press the release button on the lower right.
- Pull the storage bin out until resistance is felt. Lift up the front of the ice bin and remove.
- Press the switch to the OFF position To Replace the Ice Storage Bin:

IMPORTANT

- It may be necessary to turn the auger driver, behind the ice bin, counterclockwise to properly align the ice bin with the auger driver. The ice storage bin must be locked in place for proper ice dispensing.

Press the switch to the ON position

- Slide the ice bin into the guide rails located on either side of the enclosure.
- Push the ice bin in until resistance is felt. Raise the front slightly and push the ice bin in until an audible "click" is heard.



Ice Production Rate

- Allow 24 hours to produce the first batch of ice. Discard the first three batches of ice produced.
- The ice maker should produce approximately 8 to 12 batches of ice in a 24-hour period.
- To increase ice production, lower the freezer and refrigerator temperature.
- See "Using the Controls." Wait 24 hours between adjustments.

Remember

- The quality of your ice will be only as good as the quality of the water supplied to your ice maker. Avoid connecting the ice maker to a softened water supply. Water softener chemicals (such as salt) can damage parts of the ice maker and lead to poor quality ice. If a softened water supply cannot be avoided.
- Do not use anything sharp to break up the ice in the bin. This can cause damage to the ice bin and dispenser mechanism.
- Do not store anything on top of the ice maker or in the ice storage bin.

IMPORTANT:

- After connecting the refrigerator to a water source, flush the water system.
- Press the Water button on the dispenser control panel. Use a sturdy container to depress and hold the dispenser lever for 5 seconds, then release it for 5 seconds.
- Repeat until water begins to flow. Once water begins to flow, continue depressing and releasing the dispenser lever (5 seconds on, 5 seconds off) for an additional 2 minutes.
- This will flush air from the filter and water dispensing system.
- Additional flushing may be required in some households.
- As air is cleared from the system, water may spurt out of the dispenser.

NOTE:

- After 5 minutes of continuous dispensing, the dispenser will stop dispensing water to avoid flooding.
- To continue dispensing, remove the container and press the dispensing lever again.
- Allow 24 hours for the refrigerator to cool down and chill water. Dispense enough water every week to maintain a fresh supply.
- Allow 24 hours to produce the first batch of ice. Discard the first three batches of ice produced.

IMPORTANT:

- The dispenser will dispense either water or cubed ice, or both water and cubed ice.

- The Front Fill feature allows you to dispense water into containers that will not fit within the dispenser area. such as sport bottles.

To Dispense Water or Ice Cubes:

- Select water or cube ice by pressing the corresponding touch pad on the dispenser control panel. A light above the touch pad indicates your selection.
- Press a sturdy container against the dispenser lever.
- **IMPORTANT:** You do not need to apply a lot of pressure to the lever in order to activate the dispenser. Pressing hard will not make the water or ice dispense faster or in greater quantities.
- Remove the container to stop dispensing.

To Dispense Water and Ice Cubes Together:

- Select Cube. A light above the touch pad indicates your selection.
- Press a sturdy container against the dispenser lever while pressing the Front Fill touch pad.

IMPORTANT:

1. You do not need to apply a lot of pressure to the lever in order to activate the dispenser. Pressing hard will not make the water or ice dispense faster or in greater quantities.
2. Remove the container to stop dispensing.
3. Dispenser Light

NOTES:

- The dispenser lights are LEDs which should not need to be changed.
- When you use the dispenser. the lever will automatically turn the light on. If you want the light to be on continuously. you may choose either On or Auto.

Auto On

- **Auto:** The dispenser light will illuminate at half-power when the light sensor detects the light levels in the room are low. To turn the dispenser light on. press the Light touch pad. The Auto indicator light will illuminate.
- **On:** For continuous light. press the Light touch pad a second time. The On indicator light will illuminate.
- **Off:** To turn the dispenser light off. press the Light touch pad a third time.

DispenserLock

- The dispenser lock does not shut off power to the product. to the ice maker. or to the dispenser light. It just deactivates the dispenser lever.

To Lock and Unlock Dispenser:

- Press and hold the LocWUUnlock touch pad for three seconds to lock the dispenser. The indicator light will illuminate when Lock is on.
- Press and hold the LocWUUnlock touch pad again for three seconds to unlock dispenser. The indicator light will turn off.
- The water filter is located in the upper right-hand corner of the refrigerator compartment.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Water Filter Status Lights

- The water filter indicator lights will remind you when it is time to order and replace your water filter. When the yellow (Order) light is on, it is almost time to change the water filter. When the red (Replace) light is on, a new water filter should be installed.
- It is recommended that you replace the water filter when the indicator light changes to red OR earlier if the flow of water to your water dispenser or ice maker decreases noticeably.
- After replacing the water filter, press and hold the Reset Filter pad for three seconds.
- The Order and Replace indicator lights will blink and then go off when the system is reset.

Replacing the Water Filter

1. Turn filter counterclockwise to remove.
2. Remove sealing label from replacement filter and insert the filter end into the filter head.
3. Turn the filter clockwise until it stops.
4. Snap the filter cover closed.

NOTE:

- The dispenser feature may be used without a water filter installed.
- Your water will not be filtered. If this option is chosen, replace the filter with the blue bypass cap.

REFRIGERATORCARE

- Because air circulates between both sections, any odors formed in one section will transfer to the other.
- You must thoroughly clean both sections to eliminate odors. To avoid odor transfer and drying out of food, wrap or cover foods tightly.

To Clean Your Refrigerator:

- Do not use abrasive or harsh cleaners such as window sprays, scouring cleansers, flammable fluids, cleaning waxes, concentrated detergents, bleaches or cleansers containing petroleum products on plastic parts, interior and door liners or gaskets. Do not use paper towels, scouring pads, or other harsh cleaning tools.
- Unplug refrigerator or disconnect power.
- Hand wash, rinse, and dry removable parts and interior surfaces thoroughly.
- Use a clean sponge or soft cloth and a mild detergent in warm water.
- Wash stainless steel and painted metal exteriors with a clean sponge or soft cloth and a mild detergent in warm water.
- To keep your stainless steel refrigerator looking like new and to remove minor scuffs or marks, it is suggested that you use the manufacturer's approved Stainless Steel Cleaner and Polish, Part Number 20000008. To order the cleaner, call 1-877-232-6771 U.S.A. or 1-800-807-6777 Canada.

IMPORTANT:

- This cleaner is for stainless steel parts only!
- Do not allow the Stainless Steel Cleaner and Polish to come into contact with any plastic parts such as the trim pieces, dispenser covers or door gaskets. If unintentional contact does occur, clean plastic part with a sponge and mild detergent in warm water. Dry thoroughly with a soft cloth.
- There is no need for routine condenser cleaning in normal home operating environments.
- If the environment is particularly greasy or dusty, or there is significant pet traffic in the home, the condenser should be cleaned every 2 to 3 months to ensure maximum efficiency.
- If you need to clean the condenser:

Remove the base grille.

- Use a vacuum cleaner with a soft brush to clean the grille, the open areas behind the grille and the front surface area of the condenser.
- Replace the base grille when finished.
- Plug in refrigerator or reconnect power.

NOTE:

- Not all appliance bulbs will fit your refrigerator.
- Be sure to replace the bulb with an appliance bulb of the same size, shape, and wattage (no greater than 40 watts).

- Unplug refrigerator or disconnect power.
- Remove the light shield. if necessary.
- Top of the refrigerator compartment Squeeze both sides of the light shield while pulling downward to remove.
- Beneath ice storage enclosure Press along upper edge of light shield and roll light shield forward to remove.
- Replace burned-out bulb(s) with appliance light bulb(s) no greater than 40 watts.
- Replace the light shield(s) by inserting the tabs on the shield into the liner holes and snap into place.
- NOTE: To avoid damaging the light shield. do not force the shield beyond the locking point.
- Plug in refrigerator or reconnect power.

TROUBLESHOOTING

- Electrical Shock Hazard
- Plug into a grounded 3 prong outlet.
- Do not remove ground prong.
- Do not use an adapter.
- Do not use an extension cord.
- Failure to follow these instructions can result in death. fire. or electrical shock.
- Power cord unplugged?
- Plug into a grounded 3 prong outlet.
- Is outlet working?
- Plug in a lamp to see if the outlet is working.
- Household fuse blown or circuit breaker tripped? Replace the fuse or reset the circuit breaker.
- If the problem continues. call an electrician.
- Are controls on? Make sure the refrigerator controls are on.
- See "Using the Controls."

Explosion Hazard

- Use nonflammable cleaner.
- Failure to do so can result in death. explosion. or fire.
- Gaskets dirty or sticky? Clean gaskets and contact surfaces with mild soap and warm water. Rinse and dry with soft cloth.

- Temperature is too warm

NOTE:

- Some moisture buildup is normal.
- Humid room? Contributes to moisture buildup.
- Door(s) opened often or left open? Allows humid air to enter refrigerator.
- Minimize door openings and keep doors fully closed.
- The ice maker is not producing ice or not enough ice
- Refrigerator connected to a water supply and the supply shutoff valve turned on?
Connect refrigerator to water supply and turn water shutoff valve fully open.
- Kink in the water source line? A kink in the line can reduce water flow. Straighten the water source line.
- Ice maker turned on? Make sure wire shutoff arm or switch (depending on model) is in the ON position.

Water from the dispenser is warm

1. Water from the dispenser is only chilled to 50°F (10°C). New installation?
2. Allow 24 hours after installation for the water supply to cool completely.
3. Recently dispensed large amount of water? Allow 24 hours for water supply to cool completely.
4. Water not been recently dispensed?
5. The first glass of water may not be cool. Discard the first glass of water.
6. Refrigerator connected to a cold water pipe?
7. Make sure the refrigerator is connected to a cold water pipe. See "Water Supply Requirements."

LIMITED WARRANTY

- For one year from the date of purchase, when this major appliance is operated and maintained according to instructions attached to or furnished with the product.
- Amana brand of Whirlpool Corporation or Whirlpool Canada LP (hereafter "Amana") will pay for factory specified parts and repair labor to correct defects in materials or workmanship.
- Service must be provided by a Amana designated service company. This limited warranty is valid only in the United States or Canada and applies only when the major appliance is used in the country in which it was purchased.
- Outside the 50 United States and Canada, this limited warranty does not apply. Proof of original purchase date is required to obtain service under this limited warranty.

ITEMS EXCLUDED FROM WARRANTY

- This limited warranty does not cover:
- Service calls to correct the installation of your major appliance. to instruct you on how to use your major appliance. to replace or repair house fuses. or to correct house wiring or plumbing.
- Service calls to repair or replace appliance light bulbs. air filters or water filters. Consumable parts are excluded from warranty coverage.
- Repairs when your major appliance is used for other than normal. single-family household use or when it is used in a manner that is contrary to published user or operator instructions and/or installation instructions.
- Damage resulting from accident. alteration. misuse. abuse. fire. flood. acts of God. improper installation. installation not in accordance with electrical or plumbing codes. or use of consumables or cleaning products not approved by Amana.
- Cosmetic damage. including scratches. dents. chips or other damage to the finish of your major appliance. unless such damage results from defects in materials or workmanship and is reported to Amana within 30 days from the date of purchase.
- Any food loss due to refrigerator or freezer product failures.
- Costs associated with the removal from your home of your major appliance for repairs. This major appliance is designed to be repaired in the home and only in-home service is covered by this warranty.
- Repairs to parts or systems resulting from unauthorized modifications made to the appliance.
- Expenses for travel and transportation for product service if your major appliance is located in a remote area where service by an authorized Amana servicer is not available.

Warning

This content is compiled from multiple sources and is provided for reference purposes only. It may not be complete or fully applicable to all situations. If you are unable to resolve your issue, please contact the product manufacturer or an authorized service provider for official support.